

屋内照明器具特性	
品番 (品名)	P A Z 0 7 5 2 0 W W W P 2 7 + N T S 9 5 1 0 0
光源	L E D 2 7 0 0 _ 7 0 _ 3 9 0 × 1 3 9 0 . 0 l m
管理番号	K 0 1 9 7 3 7 8 (0) D R 1
B Z 分類	B Z 1

器具効率		1 0 0 %	反 射 率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束		0 %	室指数	照明率 (X 0 . 0 1) Z C M																		
下方光束		1 0 0 %																				
保守率		良	0 . 6 3	0 . 6	7 8	7 1	6 6	6 2	7 7	7 0	6 6	6 2	7 6	6 9	6 5	6 2	7 4	6 9	6 5	6 2	6 1	
		中	0 . 6	0 . 8	8 5	7 9	7 4	7 1	8 5	7 8	7 4	7 1	8 3	7 8	7 4	7 1	8 1	7 7	7 3	7 1	6 9	
		否	1 . 0	9 0	8 4	8 0	7 7	8 9	8 4	8 0	7 7	8 7	8 3	7 9	7 6	8 6	8 2	7 8	7 6	7 5		
		0 . 5 6	1 . 2 5	9 4	8 9	8 5	8 2	9 3	8 8	8 5	8 2	9 1	8 7	8 4	8 1	8 9	8 6	8 3	8 1	7 9		
下方投影面積		c m ²	1 . 5	9 6	9 2	8 8	8 6	9 5	9 1	8 8	8 5	9 3	9 0	8 7	8 5	9 1	8 9	8 6	8 4	8 2		
			等価発光面積	c m ²	2 . 0	1 0 0	9 6	9 3	9 1	9 8	9 5	9 2	9 0	9 6	9 4	9 1	8 9	9 4	9 2	9 0	8 8	8 7
取付 高さ	器具間隔最大限		2 . 5	1 0 1	9 8	9 6	9 4	1 0 0	9 8	9 5	9 3	9 8	9 6	9 4	9 2	9 6	9 4	9 3	9 1	8 9		
	横方向 (A)	縦方向 (B)	3 . 0	1 0 3	1 0 0	9 8	9 6	1 0 1	9 9	9 7	9 5	9 9	9 7	9 6	9 4	9 7	9 6	9 4	9 3	9 1		
H m	0 . 5 1 H m	0 . 7 8 H m	4 . 0	1 0 4	1 0 2	1 0 0	9 9	1 0 3	1 0 1	9 9	9 8	1 0 1	9 9	9 8	9 7	9 9	9 8	9 6	9 5	9 3		
			5 . 0	1 0 5	1 0 3	1 0 2	1 0 1	1 0 4	1 0 2	1 0 1	1 0 0	1 0 2	1 0 0	9 9	9 8	1 0 0	9 9	9 8	9 7	9 4		
			7 . 0	1 0 6	1 0 5	1 0 4	1 0 3	1 0 5	1 0 4	1 0 3	1 0 2	1 0 3	1 0 2	1 0 1	1 0 0	1 0 1	1 0 0	9 9	9 9	9 6		
			1 0 . 0	1 0 7	1 0 6	1 0 5	1 0 4	1 0 6	1 0 5	1 0 4	1 0 3	1 0 3	1 0 3	1 0 2	1 0 2	1 0 1	1 0 1	1 0 0	1 0 0	9 7		

