

屋内照明器具特性	
品番 (品名)	P M L C 0 6 2 7 W2 S
光源	L E D 2 7 0 0 _ 7 0 _ 1 3 1 0 x 1 1 3 1 0 . 0 l m
管理番号	K 0 1 7 8 4 7 0 (0) D Y 1
B Z 分類	B Z 1

器具効率		1 0 0 %	反 射 率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束		3 %	室指数	照明率 (X 0 . 0 1)																		Z C M
下方光束		9 7 %																				
保守率		良 中 否	0 . 6	8 2	7 5	7 1	6 8	8 1	7 5	7 1	6 8	7 9	7 4	7 0	6 8	7 8	7 3	7 0	6 8	6 6		
			0 . 8	8 8	8 2	7 8	7 5	8 7	8 1	7 7	7 5	8 5	8 0	7 7	7 4	8 3	7 9	7 6	7 4	7 2		
			1 . 0	9 1	8 6	8 2	7 9	9 0	8 5	8 2	7 9	8 8	8 4	8 1	7 8	8 6	8 3	8 0	7 8	7 6		
			0 . 6 3	1 . 2 5	9 4	9 0	8 6	8 3	9 3	8 9	8 6	8 3	9 1	8 7	8 4	8 2	8 9	8 6	8 3	8 1	7 9	
下方投影面積		c m ²	1 . 5	9 7	9 2	8 9	8 6	9 5	9 1	8 8	8 6	9 3	9 0	8 7	8 5	9 1	8 8	8 6	8 4	8 2		
			等価発光面積	c m ²	2 . 0	9 9	9 6	9 3	9 1	9 8	9 5	9 2	9 0	9 5	9 3	9 1	8 9	9 3	9 1	8 9	8 7	8 5
取付 高さ	器具間隔最大限		2 . 5	1 0 1	9 8	9 5	9 3	1 0 0	9 7	9 5	9 3	9 7	9 5	9 3	9 1	9 5	9 3	9 1	9 0	8 7		
	横方向 (A)		縦方向 (B)	3 . 0	1 0 2	9 9	9 7	9 5	1 0 1	9 8	9 6	9 5	9 8	9 6	9 4	9 3	9 6	9 4	9 3	9 1	8 9	
1 . 5 m	0 . 4 3 m	0 . 6 8 m	4 . 0	1 0 3	1 0 1	1 0 0	9 8	1 0 2	1 0 0	9 9	9 7	9 9	9 8	9 7	9 5	9 7	9 6	9 5	9 4	9 1		
2	0 . 5 4	0 . 7 5	5 . 0	1 0 4	1 0 3	1 0 1	1 0 0	1 0 3	1 0 1	1 0 0	9 9	1 0 0	9 9	9 8	9 7	9 8	9 7	9 6	9 5	9 2		
2 . 5	0 . 6 6	0 . 8 5	7 . 0	1 0 5	1 0 4	1 0 3	1 0 2	1 0 4	1 0 3	1 0 2	1 0 1	1 0 1	1 0 0	9 9	9 9	9 9	9 8	9 7	9 7	9 3		
3	0 . 7 2	0 . 8 8	1 0 . 0	1 0 6	1 0 5	1 0 5	1 0 4	1 0 5	1 0 4	1 0 3	1 0 3	1 0 2	1 0 1	1 0 1	1 0 0	9 9	9 9	9 8	9 8	9 4		

