

# 屋内照明器具特性

|         |                              |  |  |  |  |  |  |  |  |  |
|---------|------------------------------|--|--|--|--|--|--|--|--|--|
| 品番 (品名) | XF X4 5 8 GED                |  |  |  |  |  |  |  |  |  |
| 光源      | LED6500_85_4500 x1 4500.0 lm |  |  |  |  |  |  |  |  |  |
| 管理番号    | K0192153(0)D 1               |  |  |  |  |  |  |  |  |  |
| BZ分類    | BZ4                          |  |  |  |  |  |  |  |  |  |

|        |                   |                  |      |      |      |      |      |      |      |      |     |      |      |     |     |     |     |     |     |     |     |
|--------|-------------------|------------------|------|------|------|------|------|------|------|------|-----|------|------|-----|-----|-----|-----|-----|-----|-----|-----|
| 器具効率   | 100%              | 天井               | 80%  |      |      |      | 70%  |      |      |      | 50% |      |      |     | 30% |     |     |     | 0%  |     |     |
|        | 上方光束              |                  | 0%   | 反射率  | 70   | 50   | 30   | 10   | 70   | 50   | 30  | 10   | 70   | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 0%  |
|        | 下方光束              |                  | 100% |      | 床    | 10%  |      |      |      | 10%  |     |      |      | 10% |     |     |     | 10% |     |     |     |
| 室指数    | 照明率 ( X0.01 ) ZCM |                  |      |      |      |      |      |      |      |      |     |      |      |     |     |     |     |     |     |     |     |
| 保守率    | 良                 | 0.81             | 0.6  | 5.9  | 4.7  | 3.9  | 3.4  | 5.7  | 4.6  | 3.9  | 3.4 | 5.5  | 4.5  | 3.8 | 3.4 | 5.3 | 4.4 | 3.8 | 3.4 | 3.2 |     |
|        | 中                 | 0.77             | 0.8  | 6.9  | 5.8  | 5.1  | 4.5  | 6.8  | 5.7  | 5.0  | 4.5 | 6.5  | 5.6  | 5.0 | 4.5 | 6.3 | 5.5 | 4.9 | 4.5 | 4.3 |     |
|        | 否                 | 0.68             | 1.0  | 7.6  | 6.6  | 5.9  | 5.3  | 7.4  | 6.5  | 5.8  | 5.3 | 7.2  | 6.4  | 5.7 | 5.3 | 6.9 | 6.2 | 5.7 | 5.2 | 5.0 |     |
|        | 下方投影面積            | c m <sup>2</sup> |      | 1.25 | 8.2  | 7.3  | 6.6  | 6.1  | 8.0  | 7.2  | 6.6 | 6.1  | 7.7  | 7.0 | 6.5 | 6.0 | 7.5 | 6.9 | 6.4 | 6.0 | 5.8 |
| 等価発光面積 | c m <sup>2</sup>  |                  | 1.5  | 8.6  | 7.8  | 7.2  | 6.7  | 8.4  | 7.7  | 7.1  | 6.6 | 8.1  | 7.5  | 7.0 | 6.6 | 7.9 | 7.3 | 6.9 | 6.5 | 6.3 |     |
|        | c m <sup>2</sup>  |                  | 2.0  | 9.1  | 8.5  | 7.9  | 7.5  | 9.0  | 8.4  | 7.8  | 7.4 | 8.7  | 8.2  | 7.7 | 7.3 | 8.4 | 8.0 | 7.6 | 7.3 | 7.0 |     |
| 取付高さ   | 器具間隔最大限           |                  | 2.5  | 9.5  | 8.9  | 8.4  | 8.0  | 9.3  | 8.8  | 8.3  | 8.0 | 9.0  | 8.6  | 8.2 | 7.9 | 8.8 | 8.4 | 8.1 | 7.8 | 7.5 |     |
|        | 横方向 (A)           | 縦方向 (B)          | 3.0  | 9.7  | 9.2  | 8.8  | 8.4  | 9.5  | 9.1  | 8.7  | 8.3 | 9.3  | 8.9  | 8.5 | 8.2 | 9.0 | 8.7 | 8.4 | 8.1 | 7.9 |     |
| 1.5m   | 2.05m             | 2.1m             | 4.0  | 10.0 | 9.6  | 9.2  | 8.9  | 9.8  | 9.5  | 9.2  | 8.9 | 9.6  | 9.3  | 9.0 | 8.7 | 9.3 | 9.0 | 8.8 | 8.6 | 8.3 |     |
| 2      | 2.71              | 2.65             | 5.0  | 10.1 | 9.8  | 9.5  | 9.3  | 10.0 | 9.7  | 9.4  | 9.2 | 9.7  | 9.5  | 9.3 | 9.1 | 9.5 | 9.3 | 9.1 | 8.9 | 8.6 |     |
| 2.5    | 3.37              | 3.21             | 7.0  | 10.3 | 10.1 | 9.9  | 9.7  | 10.2 | 10.0 | 9.8  | 9.6 | 9.9  | 9.8  | 9.6 | 9.4 | 9.7 | 9.6 | 9.4 | 9.3 | 9.0 |     |
| 3      | 4.03              | 3.79             | 10.0 | 10.5 | 10.3 | 10.2 | 10.0 | 10.4 | 10.2 | 10.1 | 9.9 | 10.1 | 10.0 | 9.9 | 9.7 | 9.9 | 9.8 | 9.7 | 9.6 | 9.3 |     |

