

| 屋内照明器具特性 |                             |
|----------|-----------------------------|
| 品番 (品名)  | P ML L H2 0 4 9 4 K5 0      |
| 光源       | LED5000_70_260 ×1 260.0 l m |
| 管理番号     | K0178333 ( 0 ) DY 1         |
| B Z 分類   | BZ5 / 0.7 / BZ4 / 2.3 / BZ5 |

| 器具効率     |                     | 100 %           | 反射率    | 天井   | 80 %            |                   |    |     | 70 % |      |    |    | 50 % |      |    |    | 30 % |      |    |    | 0 % |     |
|----------|---------------------|-----------------|--------|------|-----------------|-------------------|----|-----|------|------|----|----|------|------|----|----|------|------|----|----|-----|-----|
|          |                     |                 |        | 壁    | 70              | 50                | 30 | 10  | 70   | 50   | 30 | 10 | 70   | 50   | 30 | 10 | 70   | 50   | 30 | 10 | 0 % |     |
|          |                     |                 |        |      | 床               | 10 %              |    |     |      | 10 % |    |    |      | 10 % |    |    |      | 10 % |    |    |     | 0 % |
|          |                     |                 |        |      |                 | 照明率 ( X0.01) Z CM |    |     |      |      |    |    |      |      |    |    |      |      |    |    |     |     |
| 保守率      |                     | 良<br>中<br>否     | 0.69   | 0.6  | 57              | 45                | 37 | 32  | 55   | 44   | 37 | 32 | 52   | 42   | 36 | 31 | 49   | 41   | 35 | 30 | 28  |     |
|          |                     |                 | 0.67   | 0.8  | 67              | 55                | 48 | 42  | 65   | 54   | 47 | 42 | 61   | 52   | 46 | 41 | 58   | 50   | 44 | 40 | 37  |     |
|          |                     |                 | 0.63   | 1.0  | 73              | 63                | 55 | 50  | 71   | 61   | 54 | 49 | 67   | 59   | 53 | 48 | 63   | 56   | 51 | 47 | 44  |     |
|          |                     |                 |        | 1.25 | 79              | 69                | 62 | 57  | 77   | 68   | 61 | 56 | 72   | 65   | 59 | 55 | 69   | 63   | 58 | 54 | 50  |     |
| 下方投影面積   |                     | cm <sup>2</sup> | 1.5    | 83   | 74              | 68                | 62 | 80  | 73   | 66   | 62 | 76 | 70   | 64   | 60 | 72 | 67   | 62   | 58 | 55 |     |     |
|          |                     |                 | 等価発光面積 |      | cm <sup>2</sup> | 2.0               | 88 | 81  | 75   | 70   | 86 | 79 | 74   | 69   | 81 | 76 | 71   | 67   | 77 | 73 | 69  | 66  |
| 取付<br>高さ | 器具間隔最大限             |                 | 2.5    | 91   | 85              | 80                | 76 | 89  | 84   | 79   | 75 | 85 | 80   | 76   | 72 | 81 | 77   | 73   | 70 | 66 |     |     |
|          | 横方向 ( A ) 縦方向 ( B ) |                 | 3.0    | 94   | 88              | 84                | 80 | 91  | 87   | 82   | 79 | 87 | 83   | 79   | 76 | 83 | 80   | 77   | 74 | 70 |     |     |
| 1.5m     | 1.88 m              | 1.91 m          | 4.0    | 97   | 92              | 89                | 85 | 94  | 91   | 87   | 84 | 90 | 87   | 84   | 81 | 86 | 83   | 81   | 79 | 74 |     |     |
| 2        | 2.5                 | 2.53            | 5.0    | 99   | 95              | 92                | 89 | 96  | 93   | 90   | 87 | 92 | 89   | 87   | 84 | 88 | 86   | 84   | 82 | 77 |     |     |
| 2.5      | 3.13                | 3.14            | 7.0    | 101  | 98              | 95                | 93 | 98  | 96   | 94   | 92 | 94 | 92   | 90   | 88 | 90 | 89   | 87   | 85 | 81 |     |     |
| 3        | 3.75                | 3.76            | 10.0   | 102  | 100             | 98                | 97 | 100 | 98   | 97   | 95 | 96 | 94   | 93   | 92 | 92 | 91   | 90   | 88 | 83 |     |     |

