

屋内照明器具特性	
品番 (品名)	XAD1121LK
光源	L LD2020LCB1 ×1 460.0 lm
管理番号	K0175528 (0) DR1
BZ分類	BZ1

器具効率			7 4 %	反 射 率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %			
					壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %			
					床	1 0 %				1 0 %				1 0 %				1 0 %				0 %			
上方光束			0 %	室指数	照明率 (X 0 . 0 1)																				Z C M
下方光束			7 4 %																						
保守率			良 中 否	0 . 6 7	0 . 6	6 1	5 7	5 4	5 1	6 1	5 6	5 3	5 1	6 0	5 6	5 3	5 1	5 9	5 5	5 3	5 1	5 0			
				0 . 6 3	0 . 8	6 6	6 1	5 9	5 7	6 5	6 1	5 8	5 7	6 4	6 1	5 8	5 6	6 3	6 0	5 8	5 6	5 5			
				0 . 5 6	1 . 0	6 8	6 5	6 2	6 0	6 8	6 4	6 2	6 0	6 7	6 4	6 1	6 0	6 5	6 3	6 1	5 9	5 8			
				1 . 2 5	7 1	6 7	6 5	6 3	7 0	6 7	6 5	6 3	6 9	6 6	6 4	6 3	6 7	6 5	6 4	6 2	6 1				
下方投影面積			c m ²	1 . 5	7 2	6 9	6 7	6 5	7 2	6 9	6 7	6 5	7 0	6 8	6 6	6 5	6 9	6 7	6 5	6 4	6 3				
				2 . 0	7 4	7 2	7 0	6 8	7 3	7 1	7 0	6 8	7 2	7 0	6 9	6 7	7 1	6 9	6 8	6 7	6 5				
取付 高さ	器具間隔最大限			2 . 5	7 5	7 3	7 2	7 0	7 5	7 3	7 1	7 0	7 3	7 2	7 0	6 9	7 2	7 0	6 9	6 8	6 7				
	横方向 (A)		縦方向 (B)	3 . 0	7 6	7 4	7 3	7 2	7 5	7 4	7 2	7 1	7 4	7 3	7 1	7 0	7 2	7 1	7 0	7 0	6 8				
H m	0 . 4 1 H m		0 . 4 1 H m	4 . 0	7 7	7 6	7 5	7 4	7 6	7 5	7 4	7 3	7 5	7 4	7 3	7 2	7 3	7 2	7 2	7 1	6 9				
				5 . 0	7 8	7 7	7 6	7 5	7 7	7 6	7 5	7 4	7 5	7 4	7 4	7 3	7 4	7 3	7 3	7 2	7 0				
				7 . 0	7 8	7 8	7 7	7 6	7 8	7 7	7 6	7 5	7 6	7 5	7 5	7 4	7 4	7 4	7 3	7 3	7 1				
				1 0 . 0	7 9	7 8	7 8	7 7	7 8	7 7	7 7	7 6	7 6	7 6	7 6	7 5	7 5	7 4	7 4	7 4	7 2				

