

屋内照明器具特性	
品番 (品名)	P ML L H2 1 2 1 4 K2 7
光源	LED2700_70_580 x1 580.0 lm
管理番号	K0178297 (0) DY 1
BZ分類	BZ5/0.7/BZ4/2.8/BZ5

器具効率	100 % 上方光束 8 % 下方光束 92 %	天井	80 %				70 %				50 %				30 %				0 %
		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
		室指数	照明率 (X0.01)																Z CM
保守率	良 0.69	0.6	57	45	37	32	55	44	37	32	52	42	36	31	49	41	35	31	28
	中 0.67	0.8	67	56	48	42	65	54	47	42	61	52	46	41	58	50	45	40	38
	否 0.63	1.0	73	63	55	50	71	62	55	49	67	59	53	48	64	57	51	47	44
		1.25	79	70	63	57	77	68	62	56	73	65	60	55	69	63	58	54	51
下方投影面積 等価発光面積	cm ²	1.5	83	74	68	63	81	73	67	62	76	70	65	60	73	67	63	59	55
		2.0	88	81	75	71	86	79	74	70	82	76	72	68	78	73	69	66	62
		2.5	92	85	80	76	89	84	79	75	85	80	76	73	81	77	74	71	67
		3.0	94	89	84	80	92	87	82	79	87	83	80	76	83	80	77	74	70
取付高さ	器具間隔最大限		4.0	97	93	89	85	95	91	87	84	90	87	84	81	86	84	81	79
	横方向 (A)		5.0	99	95	92	89	96	93	90	88	92	89	87	85	88	86	84	82
	縦方向 (B)		7.0	101	98	96	93	99	96	94	92	94	92	90	89	90	89	87	86
			10.0	102	100	99	97	100	98	97	95	96	95	93	92	92	91	90	89
1.5m	1.91 m	2.12 m																	
2	2.53	2.69																	
2.5	3.15	3.27																	
3	3.77	3.86																	

