

屋内照明器具特性	
品番 (品名)	P ML L H 4 0 1 3 4 K 2 7
光源	LED 2700_70_30 x1 30.0 l m
管理番号	K0178297 (0) DY 1
B Z 分類	BZ5 / 0.7 / BZ4 / 2.8 / BZ5

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
				床	10 %				10 %				10 %				10 %				0 %	
上方光束 下方光束		8 % 92 %	室指数	照明率 (X0.01) ZCM																		
保守率		良 中 否	0.69	0.6	57	45	37	32	55	44	37	32	52	42	36	31	49	41	35	31	28	
			0.67	0.8	67	56	48	42	65	54	47	42	61	52	46	41	58	50	45	40	38	
			0.63	1.0	73	63	55	50	71	62	55	49	67	59	53	48	64	57	51	47	44	
			0.63	1.25	79	70	63	57	77	68	62	56	73	65	60	55	69	63	58	54	51	
下方投影面積 等価発光面積		cm ² cm ²	1.5	83	74	68	63	81	73	67	62	76	70	65	60	73	67	63	59	55		
			2.0	88	81	75	71	86	79	74	70	82	76	72	68	78	73	69	66	62		
取付 高さ	器具間隔最大限		2.5	92	85	80	76	89	84	79	75	85	80	76	73	81	77	74	71	67		
	横方向 (A)	縦方向 (B)	3.0	94	89	84	80	92	87	82	79	87	83	80	76	83	80	77	74	70		
H m	1.25 H m	1.25 H m	4.0	97	93	89	85	95	91	87	84	90	87	84	81	86	84	81	79	74		
			5.0	99	95	92	89	96	93	90	88	92	89	87	85	88	86	84	82	77		
			7.0	101	98	96	93	99	96	94	92	94	92	90	89	90	89	87	86	81		
			10.0	102	100	99	97	100	98	97	95	96	95	93	92	92	91	90	89	84		

