

屋内照明器具特性	
品番 (品名)	P M L L H 4 0 4 9 4 K 2 7
光源	LED2700_70_120 ×1 120.0 l m
管理番号	K0178297 (0) DY 1
B Z 分類	BZ5 / 0.7 / BZ4 / 2.8 / BZ5

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %				
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
				床	10 %				10 %				10 %				10 %				0 %				
上方光束		8 %	室指数	照明率 (X0.01)																			Z	C	M
下方光束		92 %																							
保守率		良 中 否	0.69	0.6	57	45	37	32	55	44	37	32	52	42	36	31	49	41	35	31	28				
			0.67	0.8	67	56	48	42	65	54	47	42	61	52	46	41	58	50	45	40	38				
			0.63	1.0	73	63	55	50	71	62	55	49	67	59	53	48	64	57	51	47	44				
				1.25	79	70	63	57	77	68	62	56	73	65	60	55	69	63	58	54	51				
下方投影面積		cm ²	1.5	83	74	68	63	81	73	67	62	76	70	65	60	73	67	63	59	55					
			2.0	88	81	75	71	86	79	74	70	82	76	72	68	78	73	69	66	62					
等価発光面積	cm ²	2.5	92	85	80	76	89	84	79	75	85	80	76	73	81	77	74	71	67						
		3.0	94	89	84	80	92	87	82	79	87	83	80	76	83	80	77	74	70						
1.5m	1.88 m	1.91 m	4.0	97	93	89	85	95	91	87	84	90	87	84	81	86	84	81	79	74					
2	2.5	2.53	5.0	99	95	92	89	96	93	90	88	92	89	87	85	88	86	84	82	77					
2.5	3.12	3.13	7.0	101	98	96	93	99	96	94	92	94	92	90	89	90	89	87	86	81					
3	3.75	3.76	10.0	102	100	99	97	100	98	97	95	96	95	93	92	92	91	90	89	84					

