

| 屋内照明器具特性 |                              |
|----------|------------------------------|
| 品番 (品名)  | XF X439 NHV                  |
| 光源       | LED3500_85_3040 ×1 3040.0 lm |
| 管理番号     | K0192447 ( 0 ) DR 1          |
| BZ分類     | BZ5                          |

| 器具効率     |                     | 100 %           | 反射率  | 天井            | 80 % |    |    |     | 70 % |    |    |    | 50 % |    |    |    | 30 % |    |    |    | 0 % |  |   |   |  |   |
|----------|---------------------|-----------------|------|---------------|------|----|----|-----|------|----|----|----|------|----|----|----|------|----|----|----|-----|--|---|---|--|---|
|          |                     |                 |      | 壁             | 70   | 50 | 30 | 10  | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 0 % |  |   |   |  |   |
|          |                     |                 |      | 床             | 10 % |    |    |     | 10 % |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 0 % |  |   |   |  |   |
| 上方光束     |                     | 4 %             | 室指数  | 照明率 ( X0.01 ) |      |    |    |     |      |    |    |    |      |    |    |    |      |    |    |    |     |  | Z | C |  | M |
| 下方光束     |                     | 96 %            |      |               |      |    |    |     |      |    |    |    |      |    |    |    |      |    |    |    |     |  |   |   |  |   |
| 保守率      |                     | 良<br>中<br>否     | 0.83 | 0.6           | 55   | 43 | 35 | 30  | 54   | 42 | 35 | 30 | 51   | 41 | 34 | 29 | 49   | 40 | 33 | 29 | 27  |  |   |   |  |   |
|          |                     |                 | 0.81 | 0.8           | 65   | 54 | 46 | 40  | 63   | 53 | 45 | 39 | 60   | 51 | 44 | 39 | 57   | 49 | 43 | 38 | 36  |  |   |   |  |   |
|          |                     |                 | 0.77 | 1.0           | 72   | 61 | 53 | 47  | 70   | 60 | 52 | 47 | 66   | 58 | 51 | 46 | 63   | 56 | 50 | 45 | 42  |  |   |   |  |   |
|          |                     |                 |      | 1.25          | 78   | 68 | 60 | 54  | 76   | 66 | 59 | 54 | 72   | 64 | 58 | 53 | 68   | 62 | 56 | 52 | 49  |  |   |   |  |   |
| 下方投影面積   |                     | cm <sup>2</sup> | 1.5  | 82            | 72   | 65 | 60 | 80  | 71   | 64 | 59 | 76 | 69   | 63 | 58 | 72 | 66   | 61 | 57 | 54 |     |  |   |   |  |   |
| 等価発光面積   |                     | cm <sup>2</sup> | 2.0  | 87            | 79   | 73 | 68 | 85  | 78   | 72 | 67 | 81 | 75   | 70 | 66 | 78 | 73   | 68 | 64 | 61 |     |  |   |   |  |   |
| 取付<br>高さ | 器具間隔最大限             |                 | 2.5  | 91            | 84   | 78 | 73 | 89  | 83   | 77 | 73 | 85 | 80   | 75 | 71 | 81 | 77   | 73 | 70 | 66 |     |  |   |   |  |   |
|          | 横方向 ( A ) 縦方向 ( B ) |                 | 3.0  | 93            | 87   | 82 | 78 | 91  | 86   | 81 | 77 | 87 | 83   | 79 | 75 | 84 | 80   | 77 | 73 | 70 |     |  |   |   |  |   |
| 1.5m     | 1.96 m              | 2.1 m           | 4.0  | 96            | 92   | 87 | 84 | 94  | 90   | 86 | 83 | 91 | 87   | 84 | 81 | 87 | 84   | 81 | 79 | 75 |     |  |   |   |  |   |
| 2        | 2.58                | 2.64            | 5.0  | 98            | 94   | 91 | 87 | 97  | 93   | 89 | 86 | 93 | 90   | 87 | 84 | 89 | 87   | 84 | 82 | 78 |     |  |   |   |  |   |
| 2.5      | 3.21                | 3.2             | 7.0  | 101           | 98   | 95 | 92 | 99  | 96   | 93 | 91 | 95 | 93   | 91 | 89 | 92 | 90   | 88 | 86 | 82 |     |  |   |   |  |   |
| 3        | 3.84                | 3.77            | 10.0 | 103           | 100  | 98 | 96 | 101 | 99   | 97 | 95 | 97 | 96   | 94 | 92 | 94 | 92   | 91 | 90 | 86 |     |  |   |   |  |   |

