

屋内照明器具特性	
品番 (品名)	XAD1401
光源	LLD2000CU1 ×1 566.0 lm
管理番号	K0178953 (0) DR1
BZ分類	BZ4/2.8/BZ3

器具効率		74 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01)																Z
保守率		良 中 否	0.67	0.6	44	36	30	26	43	35	30	26	42	34	30	26	40	34	29	26	25
			0.63	0.8	52	44	39	35	51	44	38	35	49	43	38	34	47	42	37	34	33
			0.56	1.0	57	50	45	41	56	49	44	41	54	48	44	40	52	47	43	40	39
				1.25	61	55	50	46	60	54	50	46	58	53	49	46	56	52	48	46	44
下方投影面積		cm ²		1.5	64	59	54	51	63	58	54	50	61	57	53	50	59	55	52	49	48
			等価発光面積	cm ²	2.0	68	64	60	57	67	63	59	56	65	61	58	56	63	60	57	55
取付 高さ	器具間隔最大限			2.5	71	67	63	61	70	66	63	60	68	64	62	60	66	63	61	59	57
	横方向 (A) 縦方向 (B)			3.0	72	69	66	63	71	68	65	63	69	67	64	62	67	65	63	61	60
H m	1.24 H m	1.25 H m		4.0	74	72	69	67	73	71	69	67	71	69	67	66	70	68	66	65	63
				5.0	76	73	71	70	75	73	71	69	73	71	69	68	71	69	68	67	65
				7.0	77	75	74	72	76	74	73	72	74	73	72	71	72	71	70	69	67
				10.0	78	77	76	75	77	76	75	74	75	74	73	73	73	73	72	71	69

