

屋内照明器具特性	
品番 (品名)	PTSR10050KVW(1TOUBUN)
光源	LED5000_70_77 x1 77.0 l m
管理番号	K0155126 (0) DY 1
BZ分類	BZ6

器具効率 上方光束 下方光束		99 % 3 % 96 %		反射率	天井	80 %				70 %				50 %				30 %				0 %
					壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
					床	10 %				10 %				10 %				10 %				0 %
					室指数	照明率 (X0.01) ZCM																
保守率		良 中 否	0.69	0.6	52	39	31	25	50	38	30	25	47	37	29	24	45	35	29	24	22	
			0.67	0.8	61	49	40	34	60	48	40	34	56	46	39	33	53	44	38	33	30	
			0.63	1.0	68	56	47	41	66	55	47	40	62	52	45	40	59	50	44	39	36	
				1.25	74	63	54	48	72	61	53	47	68	59	52	46	64	57	51	46	43	
下方投影面積 等価発光面積		cm ² cm ²		1.5	78	68	60	53	76	66	59	53	72	64	57	52	68	61	56	51	48	
				2.0	84	75	68	62	82	73	67	61	78	71	65	60	74	68	63	59	55	
取付 高さ	器具間隔最大限			2.5	88	80	73	68	85	78	72	67	81	75	70	65	78	73	68	64	61	
	横方向 (A)		縦方向 (B)	3.0	90	83	77	72	88	82	76	71	84	79	74	70	81	76	72	68	65	
H m	1.31 H m		1.32 H m	4.0	94	88	83	79	92	87	82	78	88	84	80	76	84	81	77	74	70	
				5.0	96	91	87	83	94	90	86	82	90	87	83	80	87	84	81	78	74	
				7.0	99	95	92	88	97	94	90	87	93	90	88	85	90	87	85	83	79	
				10.0	101	98	96	93	99	97	94	92	96	93	91	89	92	90	89	87	83	

