

屋内照明器具特性	
品番 (品名)	PTSR5027KSP (1TOUBUN)
光源	LED2700_70_66 x1 66.0 l m
管理番号	K0155127 (0) DY1
BZ分類	BZ2/0.9/BZ3/2.3/BZ4/4.5/BZ5

器具効率		9 1 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
				室指数	照明率 (X 0 . 0 1) Z C M																
保守率		良 中 否	0 . 6	6 0	5 1	4 5	4 1	5 8	5 0	4 5	4 1	5 6	4 9	4 4	4 0	5 4	4 7	4 3	4 0	3 8	
			0 . 8	6 7	5 9	5 3	4 9	6 6	5 8	5 3	4 9	6 3	5 6	5 1	4 8	6 0	5 5	5 0	4 7	4 5	
			1 . 0	7 2	6 4	5 9	5 4	7 0	6 3	5 8	5 4	6 7	6 1	5 7	5 3	6 4	5 9	5 5	5 2	5 0	
			0 . 6 3	1 . 2 5	7 6	6 9	6 4	5 9	7 4	6 8	6 3	5 9	7 1	6 6	6 1	5 8	6 8	6 3	6 0	5 7	5 4
下方投影面積 等価発光面積		c m ² c m ²	1 . 5	7 9	7 2	6 7	6 3	7 7	7 1	6 6	6 2	7 4	6 9	6 4	6 1	7 0	6 6	6 3	6 0	5 7	
			2 . 0	8 3	7 7	7 2	6 8	8 1	7 5	7 1	6 8	7 7	7 3	6 9	6 6	7 4	7 0	6 7	6 4	6 1	
			2 . 5	8 5	8 0	7 6	7 2	8 3	7 8	7 4	7 1	7 9	7 5	7 2	6 9	7 6	7 3	7 0	6 7	6 4	
取付 高さ	器具間隔最大限		3 . 0	8 6	8 2	7 8	7 5	8 5	8 0	7 7	7 4	8 1	7 7	7 4	7 2	7 7	7 5	7 2	7 0	6 6	
	横方向 (A)	縦方向 (B)	4 . 0	8 9	8 5	8 2	7 9	8 7	8 3	8 0	7 8	8 3	8 0	7 8	7 5	7 9	7 7	7 5	7 3	6 9	
H m	1 . 3 4 H m	0 . 3 8 H m	5 . 0	9 0	8 7	8 4	8 1	8 8	8 5	8 2	8 0	8 4	8 2	8 0	7 8	8 1	7 9	7 7	7 5	7 1	
			7 . 0	9 2	8 9	8 7	8 5	9 0	8 7	8 5	8 3	8 6	8 4	8 2	8 1	8 2	8 1	7 9	7 8	7 4	
			1 0 . 0	9 3	9 1	8 9	8 8	9 1	8 9	8 8	8 6	8 7	8 6	8 5	8 3	8 4	8 3	8 2	8 0	7 6	

