

屋内照明器具特性	
品番 (品名)	X F L 3 2 3 S C
光源	LDL40S. N/ 14/ 26 (2600A) ×2 2600.0 lm
管理番号	K0126143 (1) DB 1
BZ分類	BZ3

器具効率		66 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
				床	10 %				10 %				10 %				10 %				0 %	
上方光束 下方光束		0 % 66 %	室指数	照明率 (X0.01) ZCM																		
保守率		良 中 否	0.81	0.6	42	35	30	27	41	34	30	27	40	34	30	27	38	33	29	27	25	
			0.77	0.8	49	42	38	35	48	42	38	35	46	41	37	35	45	40	37	34	33	
			0.68	1.0	53	47	43	40	52	47	43	40	51	46	43	40	49	45	42	40	38	
				1.25	57	52	48	45	56	51	48	45	54	50	47	45	53	49	47	44	43	
下方投影面積 等価発光面積		cm ² cm ²		1.5	59	55	51	49	58	54	51	48	57	53	50	48	55	52	50	48	46	
				2.0	62	59	56	53	61	58	55	53	60	57	55	52	58	56	54	52	51	
取付 高さ	器具間隔最大限		2.5	64	61	59	56	63	61	58	56	62	59	57	55	60	58	56	55	53		
	横方向 (A) 縦方向 (B)																					
1.5m	2.33 m	1.93 m	4.0	67	65	63	62	66	64	63	61	65	63	62	60	63	62	60	59	58		
2	3.09	2.4	5.0	68	66	65	63	67	66	64	63	65	64	63	62	64	63	62	61	59		
2.5	3.85	2.88	7.0	69	68	67	66	68	67	66	65	67	66	65	64	65	64	64	63	61		
3	4.6	3.37	10.0	70	69	68	67	69	68	67	67	67	67	66	65	66	65	65	64	62		

