

屋内照明器具特性	
品番 (品名)	X E D 3 2 0 0 N
光源	L L D 4 0 0 0 N C T 1 × 1 8 4 5 . 0 l m
管理番号	K 0 1 7 5 9 8 3 (0) D R 1
B Z 分類	B Z 3

器具効率		5 9 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
				室指数	照明率 (X 0 . 0 1)																Z C M
保守率		良 中 否	0 . 6 3	0 . 6	3 7	3 0	2 6	2 3	3 6	3 0	2 6	2 3	3 5	3 0	2 6	2 3	3 4	2 9	2 6	2 3	2 2
			0 . 6	0 . 8	4 3	3 7	3 3	3 0	4 2	3 7	3 3	3 0	4 1	3 6	3 3	3 0	4 0	3 5	3 2	3 0	2 9
			0 . 5 6	1 . 0	4 7	4 2	3 8	3 5	4 6	4 1	3 8	3 5	4 5	4 0	3 7	3 5	4 3	4 0	3 7	3 5	3 3
				1 . 2 5	5 0	4 6	4 2	3 9	5 0	4 5	4 2	3 9	4 8	4 4	4 1	3 9	4 7	4 3	4 1	3 9	3 8
下方投影面積		c m ²	1 . 5	5 3	4 8	4 5	4 3	5 2	4 8	4 5	4 2	5 0	4 7	4 4	4 2	4 9	4 6	4 4	4 2	4 0	
			等価発光面積	c m ²	2 . 0	5 5	5 2	4 9	4 7	5 5	5 1	4 9	4 7	5 3	5 0	4 8	4 6	5 2	4 9	4 7	4 6
取付 高さ	器具間隔最大限		2 . 5	5 7	5 4	5 2	5 0	5 6	5 4	5 2	5 0	5 5	5 3	5 1	4 9	5 3	5 2	5 0	4 8	4 7	
	横方向 (A) 縦方向 (B)		3 . 0	5 8	5 6	5 4	5 2	5 8	5 5	5 3	5 2	5 6	5 4	5 2	5 1	5 5	5 3	5 2	5 0	4 9	
H m	1 . 2 1 H m	1 . 2 1 H m	4 . 0	6 0	5 8	5 6	5 5	5 9	5 7	5 6	5 4	5 7	5 6	5 5	5 4	5 6	5 5	5 4	5 3	5 1	
			5 . 0	6 1	5 9	5 8	5 6	6 0	5 8	5 7	5 6	5 8	5 7	5 6	5 5	5 7	5 6	5 5	5 4	5 3	
			7 . 0	6 2	6 0	5 9	5 8	6 1	6 0	5 9	5 8	5 9	5 9	5 8	5 7	5 8	5 7	5 7	5 6	5 4	
			1 0 . 0	6 2	6 1	6 1	6 0	6 2	6 1	6 0	5 9	6 0	6 0	5 9	5 8	5 9	5 8	5 8	5 7	5 6	

