

| 屋内照明器具特性 |                              |
|----------|------------------------------|
| 品番 (品名)  | XF X440 NHW                  |
| 光源       | LED4000_85_3840 ×1 3840.0 lm |
| 管理番号     | K0192447 ( 0 ) DR 1          |
| BZ分類     | BZ5                          |

| 器具効率   |           | 100 %           | 反射率  | 天井            | 80 % |     |    |    | 70 % |    |    |    | 50 % |    |    |    | 30 % |    |    |    | 0 % |   |   |   |
|--------|-----------|-----------------|------|---------------|------|-----|----|----|------|----|----|----|------|----|----|----|------|----|----|----|-----|---|---|---|
|        |           |                 |      | 壁             | 70   | 50  | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 0 % |   |   |   |
|        |           |                 |      | 床             | 10 % |     |    |    | 10 % |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 0 % |   |   |   |
| 上方光束   |           | 4 %             | 室指数  | 照明率 ( X0.01 ) |      |     |    |    |      |    |    |    |      |    |    |    |      |    |    |    |     | Z | C | M |
| 下方光束   |           | 96 %            |      |               |      |     |    |    |      |    |    |    |      |    |    |    |      |    |    |    |     |   |   |   |
| 保守率    |           | 良<br>中<br>否     | 0.83 | 0.6           | 55   | 43  | 35 | 30 | 54   | 42 | 35 | 30 | 51   | 41 | 34 | 29 | 49   | 40 | 33 | 29 | 27  |   |   |   |
|        |           |                 | 0.81 | 0.8           | 65   | 54  | 46 | 40 | 63   | 53 | 45 | 39 | 60   | 51 | 44 | 39 | 57   | 49 | 43 | 38 | 36  |   |   |   |
|        |           |                 |      | 1.0           | 72   | 61  | 53 | 47 | 70   | 60 | 52 | 47 | 66   | 58 | 51 | 46 | 63   | 56 | 50 | 45 | 42  |   |   |   |
|        |           |                 | 0.77 | 1.25          | 78   | 68  | 60 | 54 | 76   | 66 | 59 | 54 | 72   | 64 | 58 | 53 | 68   | 62 | 56 | 52 | 49  |   |   |   |
| 下方投影面積 |           | cm <sup>2</sup> |      | 1.5           | 82   | 72  | 65 | 60 | 80   | 71 | 64 | 59 | 76   | 69 | 63 | 58 | 72   | 66 | 61 | 57 | 54  |   |   |   |
|        |           |                 |      | 2.0           | 87   | 79  | 73 | 68 | 85   | 78 | 72 | 67 | 81   | 75 | 70 | 66 | 78   | 73 | 68 | 64 | 61  |   |   |   |
| 取付高さ   | 器具間隔最大限   |                 |      | 2.5           | 91   | 84  | 78 | 73 | 89   | 83 | 77 | 73 | 85   | 80 | 75 | 71 | 81   | 77 | 73 | 70 | 66  |   |   |   |
|        | 横方向 ( A ) | 縦方向 ( B )       |      | 3.0           | 93   | 87  | 82 | 78 | 91   | 86 | 81 | 77 | 87   | 83 | 79 | 75 | 84   | 80 | 77 | 73 | 70  |   |   |   |
| 1.5m   | 1.96 m    | 2.1 m           |      | 4.0           | 96   | 92  | 87 | 84 | 94   | 90 | 86 | 83 | 91   | 87 | 84 | 81 | 87   | 84 | 81 | 79 | 75  |   |   |   |
| 2      | 2.58      | 2.64            |      | 5.0           | 98   | 94  | 91 | 87 | 97   | 93 | 89 | 86 | 93   | 90 | 87 | 84 | 89   | 87 | 84 | 82 | 78  |   |   |   |
| 2.5    | 3.21      | 3.2             |      | 7.0           | 101  | 98  | 95 | 92 | 99   | 96 | 93 | 91 | 95   | 93 | 91 | 89 | 92   | 90 | 88 | 86 | 82  |   |   |   |
| 3      | 3.84      | 3.77            |      | 10.0          | 103  | 100 | 98 | 96 | 101  | 99 | 97 | 95 | 97   | 96 | 94 | 92 | 94   | 92 | 91 | 90 | 86  |   |   |   |

