

屋内照明器具特性

品番 (品名)	XF X440NHW+FSK41020															
光源	LED4000_85_2980 x1 2980.0lm															
管理番号	K0199246(0)DR1															
BZ分類	BZ5/6.0/BZ6															

器具効率	100%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束	12%	室指数	照明率 (X0.01)																ZCM		
下方光束	88%																				
保守率	良 中 否	0.81	0.6	5.5	4.3	3.5	2.9	5.3	4.2	3.4	2.9	4.9	4.0	3.3	2.8	4.6	3.8	3.2	2.8	2.5	
		0.77	0.8	6.4	5.2	4.4	3.8	6.2	5.1	4.3	3.8	5.8	4.8	4.2	3.7	5.4	4.6	4.0	3.6	3.3	
			1.0	7.0	5.9	5.1	4.5	6.8	5.7	5.0	4.4	6.3	5.5	4.8	4.3	5.9	5.2	4.6	4.2	3.8	
		0.68	1.25	7.6	6.5	5.8	5.2	7.3	6.4	5.7	5.1	6.8	6.0	5.4	4.9	6.4	5.7	5.2	4.8	4.4	
下方投影面積	c m ²	1.5	7.9	7.0	6.3	5.7	7.7	6.8	6.1	5.6	7.2	6.5	5.9	5.4	6.7	6.1	5.6	5.2	4.8		
		2.0	8.5	7.7	7.0	6.5	8.2	7.5	6.9	6.4	7.7	7.1	6.6	6.1	7.2	6.7	6.3	5.9	5.4		
取付高さ	器具間隔最大限		2.5	8.8	8.1	7.5	7.0	8.6	7.9	7.4	6.9	8.0	7.5	7.0	6.6	7.6	7.1	6.7	6.4	5.9	
	横方向 (A)	縦方向 (B)	3.0	9.1	8.5	7.9	7.4	8.8	8.2	7.7	7.3	8.3	7.8	7.4	7.0	7.8	7.4	7.1	6.7	6.2	
1.5m	1.59m	2.09m	4.0	9.4	8.9	8.4	8.0	9.1	8.7	8.2	7.9	8.6	8.2	7.9	7.5	8.1	7.8	7.5	7.2	6.7	
2	2.1	2.63	5.0	9.6	9.2	8.8	8.4	9.3	8.9	8.6	8.2	8.8	8.5	8.2	7.9	8.3	8.1	7.8	7.6	7.0	
2.5	2.61	3.19	7.0	9.8	9.5	9.2	8.9	9.6	9.3	9.0	8.7	9.1	8.8	8.6	8.3	8.6	8.4	8.2	8.0	7.4	
3	3.12	3.76	10.0	10.0	9.8	9.5	9.3	9.8	9.5	9.3	9.1	9.3	9.1	8.9	8.7	8.8	8.6	8.5	8.3	7.7	

