

| 屋内照明器具特性 |                          |
|----------|--------------------------|
| 品番 (品名)  | SLB15180+SLK22004+SLK290 |
| 光源       | LLD2411LCB1 ×1 500.0 lm  |
| 管理番号     | K0193247 (3) DB1         |
| BZ分類     | BZ1/0.9/BZ2/2.8/BZ3      |

| 器具効率             |                    | 87 %<br><br>上方光束<br>14 %<br>下方光束<br>73 % | 反射率  | 天井   | 80 %             |    |    |    | 70 % |    |    |    | 50 % |    |    |    | 30 % |    |    |    | 0 % |    |
|------------------|--------------------|------------------------------------------|------|------|------------------|----|----|----|------|----|----|----|------|----|----|----|------|----|----|----|-----|----|
|                  |                    |                                          |      | 壁    | 70               | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 0 % |    |
|                  |                    |                                          |      | 床    | 10 %             |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 0 % |    |
|                  |                    |                                          |      | 室指数  | 照明率 ( X0.01) ZCM |    |    |    |      |    |    |    |      |    |    |    |      |    |    |    |     |    |
| 保守率              |                    | 良<br>中<br>否                              | 0.63 | 0.6  | 0.6              | 59 | 51 | 46 | 43   | 57 | 50 | 46 | 42   | 54 | 48 | 44 | 42   | 52 | 47 | 43 | 41  | 38 |
|                  |                    |                                          | 0.6  | 0.8  | 65               | 58 | 53 | 50 | 64   | 57 | 52 | 49 | 60   | 55 | 51 | 48 | 57   | 52 | 49 | 46 | 44  |    |
|                  |                    |                                          | 0.56 | 1.0  | 70               | 63 | 58 | 54 | 68   | 61 | 57 | 54 | 64   | 59 | 55 | 52 | 60   | 56 | 53 | 50 | 47  |    |
|                  |                    |                                          |      | 1.25 | 73               | 67 | 63 | 59 | 71   | 66 | 61 | 58 | 67   | 62 | 59 | 56 | 63   | 60 | 57 | 54 | 51  |    |
| 下方投影面積<br>等価発光面積 |                    | cm <sup>2</sup><br><br>cm <sup>2</sup>   | 1.5  | 76   | 70               | 66 | 62 | 74 | 69   | 65 | 61 | 69 | 65   | 62 | 59 | 65 | 62   | 59 | 57 | 53 |     |    |
|                  |                    |                                          | 2.0  | 79   | 75               | 71 | 68 | 77 | 73   | 69 | 66 | 72 | 69   | 66 | 64 | 68 | 65   | 63 | 61 | 57 |     |    |
|                  |                    |                                          | 2.5  | 81   | 77               | 74 | 71 | 79 | 75   | 72 | 69 | 74 | 71   | 69 | 67 | 70 | 68   | 66 | 64 | 59 |     |    |
|                  |                    |                                          | 3.0  | 83   | 79               | 76 | 74 | 80 | 77   | 74 | 72 | 76 | 73   | 71 | 69 | 71 | 69   | 67 | 66 | 61 |     |    |
| H <sub>m</sub>   | 0.77H <sub>m</sub> | 0.77H <sub>m</sub>                       | 4.0  | 85   | 82               | 79 | 77 | 82 | 80   | 77 | 75 | 77 | 75   | 73 | 72 | 73 | 71   | 70 | 68 | 63 |     |    |
|                  |                    |                                          | 5.0  | 86   | 84               | 81 | 79 | 83 | 81   | 79 | 77 | 79 | 77   | 75 | 74 | 74 | 73   | 71 | 70 | 64 |     |    |
|                  |                    |                                          | 7.0  | 87   | 86               | 84 | 82 | 85 | 83   | 82 | 80 | 80 | 79   | 77 | 76 | 75 | 74   | 73 | 72 | 66 |     |    |
|                  |                    |                                          | 10.0 | 88   | 87               | 86 | 85 | 86 | 85   | 83 | 82 | 81 | 80   | 79 | 78 | 76 | 75   | 75 | 74 | 68 |     |    |

