

屋内照明器具特性

品番 (品名)	XF X4 4 0 J HN	
光源	LED5000_85_3240 x1	3240.0 lm
管理番号	K0194260(0)DB1	
BZ分類	BZ4	

器具効率	100%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	0%	反射率	床	10%				10%				10%				10%				0%
下方光束	100%		室指数	照明率 (X0.01)																ZCM
保守率	良	0.83	0.6	5.9	4.7	3.9	3.4	5.7	4.6	3.9	3.4	5.5	4.5	3.9	3.4	5.3	4.4	3.8	3.4	3.2
	中	0.81	0.8	6.9	5.8	5.1	4.5	6.8	5.7	5.0	4.5	6.5	5.6	5.0	4.5	6.3	5.5	4.9	4.5	4.3
	否	0.77	1.0	7.6	6.6	5.9	5.3	7.4	6.5	5.8	5.3	7.2	6.4	5.7	5.3	6.9	6.2	5.7	5.2	5.0
			1.25	8.2	7.3	6.6	6.1	8.0	7.2	6.6	6.1	7.8	7.0	6.5	6.0	7.5	6.9	6.4	6.0	5.8
下方投影面積		cm ²	1.5	8.6	7.8	7.2	6.7	8.5	7.7	7.1	6.7	8.2	7.5	7.0	6.6	7.9	7.4	6.9	6.5	6.3
等価発光面積		cm ²	2.0	9.2	8.5	8.0	7.5	9.0	8.4	7.9	7.5	8.7	8.2	7.8	7.4	8.5	8.0	7.6	7.3	7.1
取付高さ	器具間隔最大限		2.5	9.5	8.9	8.5	8.1	9.3	8.8	8.4	8.0	9.1	8.6	8.3	7.9	8.8	8.4	8.1	7.8	7.6
	横方向 (A)	縦方向 (B)	3.0	9.7	9.2	8.8	8.5	9.6	9.1	8.8	8.4	9.3	8.9	8.6	8.3	9.0	8.7	8.4	8.2	7.9
1.5m	1.95m	2.11m	4.0	10.0	9.6	9.3	9.0	9.9	9.5	9.2	8.9	9.6	9.3	9.0	8.8	9.3	9.1	8.9	8.7	8.4
2	2.57	2.67	5.0	10.2	9.9	9.6	9.3	10.0	9.8	9.5	9.3	9.8	9.5	9.3	9.1	9.5	9.3	9.1	9.0	8.7
2.5	3.2	3.24	7.0	10.4	10.1	9.9	9.7	10.2	10.0	9.8	9.7	10.0	9.8	9.6	9.5	9.7	9.6	9.5	9.3	9.1
3	3.83	3.83	10.0	10.5	10.3	10.2	10.0	10.4	10.2	10.1	10.0	10.1	10.0	9.9	9.8	9.9	9.8	9.7	9.6	9.3

