

屋内照明器具特性	
品番 (品名)	XAS3503V
光源	LED3500_70_460 ×1 460.0 lm
管理番号	K0170905 (0) DB1
BZ分類	BZ3/2.8/BZ2/4.5/BZ3/6.0/BZ2

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束		0 %	室指数	照明率 (X 0 . 0 1) Z C M																		
下方光束				1 0 0 %																		
保守率		良 中 否	0 . 6 7	0 . 6	6 3	5 2	4 6	4 1	6 2	5 2	4 5	4 1	6 0	5 1	4 5	4 1	5 8	5 0	4 4	4 0	3 9	
			0 . 6 3	0 . 8	7 4	6 4	5 7	5 3	7 2	6 3	5 7	5 3	7 0	6 2	5 7	5 2	6 8	6 1	5 6	5 2	5 0	
			0 . 5 6	1 . 0	8 0	7 2	6 6	6 1	7 9	7 1	6 5	6 1	7 7	7 0	6 4	6 0	7 4	6 8	6 4	6 0	5 8	
				1 . 2 5	8 6	7 9	7 3	6 9	8 5	7 8	7 2	6 8	8 2	7 6	7 2	6 8	8 0	7 5	7 1	6 7	6 5	
下方投影面積		c m ²	1 . 5	9 0	8 3	7 8	7 4	8 8	8 2	7 7	7 3	8 6	8 1	7 6	7 3	8 3	7 9	7 5	7 2	7 0		
等価発光面積			c m ²	2 . 0	9 5	8 9	8 5	8 1	9 3	8 8	8 4	8 1	9 1	8 6	8 3	8 0	8 8	8 5	8 2	7 9	7 7	
取付 高さ	器具間隔最大限		2 . 5	9 7	9 3	8 9	8 6	9 6	9 2	8 8	8 5	9 4	9 0	8 7	8 4	9 1	8 8	8 6	8 3	8 1		
	横方向 (A) 縦方向 (B)		3 . 0	9 9	9 5	9 2	8 9	9 8	9 4	9 1	8 9	9 5	9 2	9 0	8 7	9 3	9 1	8 8	8 6	8 4		
H m	1 . 2 2 H m	1 . 2 2 H m	4 . 0	1 0 2	9 9	9 6	9 4	1 0 0	9 8	9 5	9 3	9 8	9 5	9 3	9 1	9 5	9 4	9 2	9 0	8 8		
			5 . 0	1 0 3	1 0 1	9 8	9 6	1 0 2	9 9	9 7	9 5	9 9	9 7	9 6	9 4	9 7	9 5	9 4	9 3	9 0		
			7 . 0	1 0 5	1 0 3	1 0 1	9 9	1 0 3	1 0 2	1 0 0	9 9	1 0 1	9 9	9 8	9 7	9 9	9 7	9 6	9 5	9 3		
			1 0 . 0	1 0 6	1 0 4	1 0 3	1 0 2	1 0 4	1 0 3	1 0 2	1 0 1	1 0 2	1 0 1	1 0 0	9 9	1 0 0	9 9	9 8	9 7	9 5		

