

屋内照明器具特性	
品番 (品名)	XF X4 1 0 T E W
光源	LED4000_85_1860 x1 1860.0 lm
管理番号	K0192145(0)D 1
BZ分類	BZ5

器具効率	100%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	0%	床	10%				10%				10%				10%				0%	
下方光束	100%	室指数	照明率 (X0.01)																ZCM	
保守率	良	0.83	0.6	5.6	4.4	3.6	3.0	5.5	4.3	3.5	3.0	5.2	4.2	3.5	3.0	5.0	4.1	3.4	3.0	2.8
	中	0.81	0.8	6.6	5.4	4.6	4.0	6.4	5.3	4.6	4.0	6.1	5.2	4.5	4.0	5.9	5.0	4.4	3.9	3.7
	否	0.77	1.0	7.2	6.1	5.3	4.7	7.1	6.0	5.3	4.7	6.8	5.9	5.2	4.7	6.5	5.7	5.1	4.6	4.4
			1.25	7.8	6.8	6.0	5.5	7.7	6.7	6.0	5.4	7.3	6.5	5.9	5.4	7.0	6.4	5.8	5.3	5.1
下方投影面積		cm ²	1.5	8.2	7.3	6.6	6.0	8.1	7.2	6.5	6.0	7.7	7.0	6.4	5.9	7.4	6.8	6.3	5.9	5.6
等価発光面積		cm ²	2.0	8.8	8.0	7.4	6.8	8.6	7.9	7.3	6.8	8.3	7.7	7.2	6.7	8.0	7.5	7.0	6.6	6.4
取付高さ	器具間隔最大限		2.5	9.2	8.5	7.9	7.4	9.0	8.4	7.8	7.4	8.7	8.1	7.7	7.3	8.4	7.9	7.5	7.2	6.9
	横方向 (A)	縦方向 (B)	3.0	9.4	8.8	8.3	7.8	9.2	8.7	8.2	7.8	8.9	8.5	8.0	7.7	8.6	8.2	7.9	7.6	7.3
1.5m	1.96m	2.1m	4.0	9.7	9.2	8.8	8.4	9.6	9.1	8.7	8.4	9.3	8.9	8.5	8.2	9.0	8.7	8.4	8.1	7.8
2	2.58	2.64	5.0	9.9	9.5	9.1	8.8	9.8	9.4	9.0	8.7	9.5	9.2	8.9	8.6	9.2	8.9	8.7	8.5	8.2
2.5	3.21	3.2	7.0	10.2	9.8	9.6	9.3	10.0	9.7	9.5	9.2	9.7	9.5	9.3	9.0	9.5	9.3	9.1	8.9	8.6
3	3.84	3.78	10.0	10.3	10.1	9.9	9.7	10.2	10.0	9.8	9.6	9.9	9.8	9.6	9.4	9.7	9.5	9.4	9.2	8.9

