

屋内照明器具特性

品番 (品名)	XF X450CED															
光源	LED6500_85_4860 x1 4860.0 lm															
管理番号	K0192157(0)D 1															
BZ分類	BZ6															

器具効率	100%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	17%	反射率	床	10%				10%				10%				10%				0%
下方光束	83%		室指数	照明率 (X0.01) ZCM																
保守率	良 中 否 0.83 0.81 0.77	0.6	51	39	31	25	49	37	30	24	45	35	28	23	41	33	27	22	19	
		0.8	60	48	40	34	58	47	39	33	53	44	37	32	49	41	35	30	26	
		1.0	67	55	47	40	64	53	45	39	59	50	43	38	54	46	40	36	32	
		1.25	72	62	53	47	69	60	52	46	64	56	49	44	59	52	46	42	37	
下方投影面積	c m ²	1.5	77	66	59	52	73	64	57	51	68	60	54	49	62	56	51	46	41	
		2.0	82	73	66	60	79	71	64	59	73	66	61	56	67	62	57	53	48	
取付高さ	器具間隔最大限		2.5	86	78	72	66	83	76	70	64	76	71	66	61	71	66	62	58	52
	横方向 (A)	縦方向 (B)	3.0	88	82	76	71	85	79	73	69	79	74	69	65	73	69	65	62	55
1.5m	1.97m	2.11m	4.0	92	86	81	77	89	83	79	75	82	78	74	71	76	73	70	67	60
2	2.59	2.64	5.0	94	89	85	81	91	86	82	79	85	81	78	74	79	76	73	70	64
2.5	3.23	3.2	7.0	97	93	89	86	93	90	87	84	87	84	82	79	81	79	77	75	68
3	3.85	3.78	10.0	99	96	93	91	96	93	90	88	89	87	85	83	84	82	80	79	71

