

屋内照明器具特性

品番 (品名) S L B 1 5 1 8 0 + S L K 2 2 0 0 9 + S L K 2 9 0

光源 L L D 2 4 2 1 L C B 1 × 1 5 0 0 . 0 l m

管理番号 K 0 1 9 3 6 9 2 (0) D B 1

B Z 分類 B Z 1 / 1 . 1 / B Z 2 / 3 . 5 / B Z 3

器具効率	93 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
			床	10 %				10 %				10 %				10 %				0 %
上方光束	9 %	室指数	照 明 率 (X 0 . 0 1)																	Z C M
下方光束	84 %																			

			照度 (lx) (X 0 . 0 1) Z C M																		
保守率	良 中 否	0 . 6 3	0 . 6	6 6	5 8	5 3	5 0	6 5	5 8	5 3	5 0	6 3	5 6	5 2	4 9	6 0	5 5	5 1	4 9	4 7	
		0 . 6	0 . 8	7 3	6 5	6 0	5 7	7 1	6 5	6 0	5 6	6 8	6 3	5 9	5 6	6 6	6 1	5 8	5 5	5 3	
		0 . 5 6	1 . 0	7 7	7 0	6 5	6 2	7 5	6 9	6 5	6 1	7 2	6 7	6 3	6 0	6 9	6 5	6 2	5 9	5 7	
下方投影面積		c m ²	1 . 2 5	8 1	7 5	7 0	6 6	7 9	7 3	6 9	6 6	7 6	7 1	6 7	6 4	7 3	6 9	6 6	6 3	6 0	
等価発光面積			1 . 5	8 3	7 8	7 3	7 0	8 1	7 6	7 2	6 9	7 8	7 4	7 0	6 8	7 5	7 1	6 9	6 6	6 3	
			2 . 0	8 7	8 2	7 8	7 5	8 5	8 0	7 7	7 4	8 1	7 8	7 5	7 2	7 8	7 5	7 2	7 0	6 7	
取付高さ	器具間隔最大限		2 . 5	8 9	8 5	8 1	7 8	8 7	8 3	8 0	7 7	8 3	8 0	7 7	7 5	8 0	7 7	7 5	7 3	7 0	
	横方向 (A)	縦方向 (B)	3 . 0	9 0	8 7	8 3	8 1	8 8	8 5	8 2	8 0	8 4	8 2	7 9	7 7	8 1	7 9	7 7	7 5	7 1	
H _m	0 . 4 8 H _m	0 . 5 1 H _m	4 . 0	9 2	8 9	8 7	8 4	9 0	8 7	8 5	8 3	8 6	8 4	8 2	8 0	8 3	8 1	7 9	7 8	7 4	
			5 . 0	9 3	9 1	8 8	8 6	9 1	8 9	8 7	8 5	8 7	8 6	8 4	8 2	8 4	8 2	8 1	8 0	7 5	
			7 . 0	9 5	9 3	9 1	8 9	9 3	9 1	8 9	8 8	8 9	8 7	8 6	8 5	8 5	8 4	8 3	8 2	7 7	
			1 0 . 0	9 6	9 4	9 3	9 1	9 4	9 2	9 1	9 0	9 0	8 9	8 8	8 7	8 6	8 5	8 4	8 4	7 9	

配光曲線

ランプ光束 1 0 0 0 l m

— 管軸に垂直 (A)
--- 管軸に平行 (B)

直射水平面照度

ランプ光束 1 0 0 0 l m

8 0 l x X 1 0 0

