

屋内照明器具特性	
品番 (品名)	XAD3460V
光源	LLD3020VCB1 ×1 795.0 lm
管理番号	K0175559 (0) DR1
BZ分類	BZ1

器具効率		88 %	反射率	天井	80 %				70 %				50 %				30 %				0 %			
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
				床	10 %				10 %				10 %				10 %				0 %			
上方光束		0 %	室指数	照明率 (X0.01)																			ZCM	
下方光束		88 %																						
保守率		良 中 否	0.67	0.6	73	67	63	61	72	67	63	61	71	66	63	61	70	66	63	61	60			
			0.63	0.8	78	73	69	67	77	72	69	67	76	72	69	66	74	71	68	66	65			
			0.56	1.0	81	76	73	71	80	76	73	71	79	75	72	70	77	74	72	70	69			
				1.25	84	80	77	74	83	79	76	74	81	78	76	74	80	77	75	73	72			
下方投影面積		c m ²		1.5	86	82	79	77	85	81	79	77	83	80	78	76	81	79	77	75	74			
等価発光面積			c m ²	2.0	88	85	83	80	87	84	82	80	85	83	81	79	84	82	80	79	77			
取付 高さ	器具間隔最大限		2.5	89	87	85	83	88	86	84	82	87	85	83	82	85	83	82	81	79				
	横方向 (A)		縦方向 (B)	3.0	90	88	86	85	89	87	86	84	88	86	84	83	86	84	83	82	80			
H m	0.41 H m	0.41 H m	4.0	92	90	88	87	91	89	88	86	89	87	86	85	87	86	85	84	82				
			5.0	92	91	90	88	91	90	89	88	89	88	87	86	88	87	86	85	83				
			7.0	93	92	91	90	92	91	90	89	90	89	89	88	88	88	87	87	84				
			10.0	94	93	92	92	93	92	91	91	91	90	90	89	89	89	88	88	85				

