

屋内照明器具特性	
品番 (品名)	XAD5 1 0 1 L
光源	LLD5000LCC1 ×1 1140.0 lm
管理番号	K0187675 (2) DR 1
B Z 分類	BZ2

器具効率		80 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) ZCM																
保守率		良 中 否	0.67	0.6	53	46	40	37	53	45	40	37	51	44	40	37	50	44	40	37	35
			0.63	0.8	62	55	50	46	61	54	50	46	59	53	49	46	57	52	49	46	44
			0.56	1.0	67	61	56	53	66	60	56	53	64	59	55	52	62	58	55	52	51
				1.25	71	66	61	58	70	65	61	58	68	64	60	58	66	63	60	57	56
下方投影面積 等価発光面積		cm ² cm ²		1.5	74	69	65	62	73	68	65	62	71	67	64	61	69	66	63	61	59
				2.0	77	73	70	67	76	72	70	67	74	71	69	66	72	70	68	66	64
				2.5	79	76	73	71	78	75	73	70	76	74	72	70	74	72	70	69	67
取付 高さ	器具間隔最大限		3.0	80	78	75	73	79	77	75	73	78	75	73	72	76	74	72	71	69	
	横方向 (A)	縦方向 (B)																			
H m	1.23 H m	1.23 H m	4.0	82	80	78	76	81	79	77	76	79	78	76	75	77	76	75	74	72	
			5.0	83	81	80	78	82	80	79	78	80	79	78	76	78	77	76	75	73	
			7.0	84	83	82	81	83	82	81	80	81	80	79	79	80	79	78	77	75	
			10.0	85	84	83	82	84	83	82	82	82	81	81	80	80	80	79	79	77	

