

屋内照明器具特性

品番 (品名)	XF X4 5 0 ME D									
光源	LED6500_85_4600 x1 4600.0 1 m									
管理番号	K0193032 (0) DB 1									
B Z 分類	B Z 4									

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
		床	10 %				10 %				10 %				10 %				0 %	
上方光束	0 %																			
下方光束	100 %																			
室指数	照明率 (X0.01)																ZCM			
保守率	良 中 否	0.81	0.6	5.9	4.7	4.0	3.5	5.8	4.7	4.0	3.4	5.5	4.6	3.9	3.4	5.3	4.5	3.9	3.4	3.2
		0.77	0.8	6.9	5.8	5.1	4.6	6.8	5.8	5.1	4.6	6.5	5.6	5.0	4.5	6.3	5.5	4.9	4.5	4.3
		0.68	1.0	7.6	6.6	5.9	5.4	7.5	6.5	5.9	5.3	7.2	6.4	5.8	5.3	6.9	6.2	5.7	5.3	5.1
			1.25	8.2	7.3	6.6	6.1	8.0	7.2	6.6	6.1	7.8	7.0	6.5	6.0	7.5	6.9	6.4	6.0	5.8
下方投影面積		cm ²																		
等価発光面積		cm ²																		
取付高さ	器具間隔最大限																			
	横方向 (A)	縦方向 (B)																		
1.5m	1.99 m	2.13 m	4.0	10.0	9.6	9.2	8.9	9.8	9.5	9.1	8.9	9.6	9.3	9.0	8.7	9.3	9.0	8.8	8.6	8.3
2	2.63	2.68	5.0	10.1	9.8	9.5	9.3	10.0	9.7	9.4	9.2	9.7	9.5	9.3	9.0	9.5	9.3	9.1	8.9	8.6
2.5	3.28	3.25	7.0	10.3	10.1	9.9	9.7	10.2	10.0	9.8	9.6	9.9	9.8	9.6	9.4	9.7	9.5	9.4	9.3	9.0
3	3.91	3.84	10.0	10.5	10.3	10.2	10.0	10.4	10.2	10.0	9.9	10.1	10.0	9.8	9.7	9.9	9.8	9.7	9.6	9.3

