

屋内照明器具特性

品番 (品名)	XF X4 6 9 VHN									
光源	LED5000_85_6680 x1 6680.0 lm									
管理番号	K0192147(0)D 1									
BZ分類	BZ5									

器具効率	100%	天井	80%				70%				50%				30%				0%			
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%			
上方光束	0%	床	10%				10%				10%				10%				0%			
下方光束	100%	室指数	照明率 (X0.01) ZCM																			
保守率	良 中 否 0.81 0.77 0.68	0.6	56	44	36	31	55	43	36	31	53	42	35	30	50	41	35	30	28			
		0.8	66	55	47	41	65	54	46	41	62	52	46	40	59	51	45	40	38			
		1.0	73	62	54	48	71	61	54	48	68	59	53	48	66	58	52	47	45			
		1.25	79	69	62	56	77	68	61	55	74	66	60	55	71	64	59	55	52			
下方投影面積	cm ²	1.5	83	74	67	61	81	73	66	61	78	71	65	61	75	69	64	60	58			
		2.0	89	81	75	70	87	80	74	70	84	78	73	69	81	76	72	68	65			
取付高さ	器具間隔最大限		2.5	92	86	80	76	91	85	80	75	88	83	78	74	85	81	77	73	71		
	横方向 (A)	縦方向 (B)	3.0	95	89	84	80	93	88	84	80	90	86	82	79	88	84	81	78	75		
1.5m	1.96m	2.11m	4.0	98	94	90	86	97	93	89	86	94	90	87	84	91	88	86	83	80		
2	2.59	2.65	5.0	100	97	93	90	99	95	92	89	96	93	90	88	93	91	89	87	84		
2.5	3.22	3.22	7.0	103	100	97	95	101	99	96	94	98	96	94	92	96	94	92	91	88		
3	3.85	3.8	10.0	104	102	100	99	103	101	99	98	100	99	97	96	98	97	95	94	91		

