

屋内照明器具特性

品番 (品名)	S F X 5 0 2																		
光源	LED2700_70_1225 x1 1225.0 lm																		
管理番号	K0160351 (0) DR 1																		
B Z 分類	B Z 1 0																		

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束 下方光束		8 5 % 1 5 %	室指数	照明率 (X 0 . 0 1) Z C M																		
保守率		良 中 否	0 . 6 3	0 . 6	4 3	3 1	2 4	1 9	3 7	2 7	2 1	1 7	2 6	2 0	1 5	1 2	1 7	1 2	1 0	7	0	
			0 . 6	0 . 8	5 0	3 9	3 2	2 6	4 4	3 4	2 8	2 3	3 1	2 5	2 0	1 7	2 0	1 6	1 3	1 1	1	
			0 . 5 6	1 . 0	5 6	4 5	3 8	3 2	4 8	4 0	3 3	2 9	3 5	2 9	2 4	2 1	2 2	1 8	1 5	1 3	1	
				1 . 2 5	6 1	5 1	4 4	3 9	5 3	4 5	3 9	3 4	3 8	3 3	2 8	2 5	2 4	2 1	1 8	1 6	2	
下方投影面積		c m ²	1 . 5	6 5	5 6	4 9	4 4	5 6	4 9	4 3	3 8	4 1	3 6	3 1	2 8	2 6	2 3	2 0	1 8	3		
等価発光面積			c m ²	2 . 0	7 0	6 2	5 6	5 1	6 1	5 5	4 9	4 5	4 4	4 0	3 6	3 3	2 9	2 6	2 3	2 1	4	
取付 高さ	器具間隔最大限		2 . 5	7 3	6 7	6 1	5 6	6 4	5 8	5 4	5 0	4 7	4 3	3 9	3 7	3 0	2 8	2 6	2 4	5		
	横方向 (A) 縦方向 (B)		3 . 0	7 6	7 0	6 5	6 0	6 6	6 1	5 7	5 3	4 8	4 5	4 2	3 9	3 2	2 9	2 7	2 6	6		
1 . 5m	0 m	0 m	4 . 0	7 9	7 4	7 0	6 6	6 9	6 5	6 1	5 8	5 1	4 8	4 5	4 3	3 3	3 2	3 0	2 8	7		
2	0	0	5 . 0	8 1	7 6	7 3	6 9	7 1	6 7	6 4	6 1	5 2	5 0	4 8	4 5	3 5	3 3	3 1	3 0	8		
2 . 5	0	0 . 5	7 . 0	8 3	8 0	7 7	7 4	7 3	7 0	6 8	6 5	5 4	5 2	5 0	4 9	3 6	3 5	3 4	3 2	9		
3	0	0 . 6	1 0 . 0	8 5	8 2	8 0	7 8	7 5	7 3	7 1	6 9	5 5	5 4	5 3	5 1	3 7	3 6	3 5	3 4	1 0		

