

屋内照明器具特性	
品番 (品名)	XF Y6 6 0 0 C
光源	LDL40S.N/29/38(3800A) ×6      3800.0 l m
管理番号	K0125273(0)DC1
BZ分類	BZ5

器具効率	61%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	1%	床	10%				10%				10%				10%				0%	
下方光束	60%	室指数	照明率 ( X0.01 )																ZCM	
保守率	良	0.86	0.6	3.4	2.7	2.2	1.9	3.4	2.7	2.2	1.9	3.2	2.6	2.2	1.9	3.1	2.5	2.1	1.9	1.8
	中	0.81	0.8	4.0	3.3	2.9	2.5	3.9	3.3	2.8	2.5	3.8	3.2	2.8	2.5	3.6	3.1	2.8	2.5	2.4
	否	0.76	1.0	4.4	3.8	3.3	3.0	4.3	3.7	3.3	3.0	4.2	3.6	3.2	2.9	4.0	3.5	3.2	2.9	2.8
			1.25	4.8	4.2	3.8	3.4	4.7	4.1	3.7	3.4	4.5	4.0	3.7	3.4	4.3	3.9	3.6	3.3	3.2
下方投影面積		cm <sup>2</sup>	1.5	5.0	4.5	4.1	3.8	4.9	4.4	4.1	3.7	4.7	4.3	4.0	3.7	4.6	4.2	3.9	3.7	3.5
等価発光面積		cm <sup>2</sup>	2.0	5.4	4.9	4.6	4.3	5.3	4.9	4.5	4.2	5.1	4.7	4.4	4.2	4.9	4.6	4.3	4.1	4.0
取付高さ	器具間隔最大限		2.5	5.6	5.2	4.9	4.6	5.5	5.1	4.8	4.6	5.3	5.0	4.7	4.5	5.1	4.9	4.6	4.4	4.3
	横方向 (A)	縦方向 (B)	3.0	5.7	5.4	5.1	4.9	5.6	5.3	5.1	4.8	5.5	5.2	5.0	4.7	5.3	5.1	4.9	4.7	4.5
1.5m	2.32m	2.28m	4.0	5.9	5.7	5.4	5.2	5.8	5.6	5.4	5.2	5.6	5.4	5.2	5.1	5.5	5.3	5.1	5.0	4.8
2	2.85	2.79	5.0	6.0	5.8	5.6	5.4	5.9	5.7	5.5	5.4	5.8	5.6	5.4	5.3	5.6	5.5	5.3	5.2	5.0
2.5	3.41	3.34	7.0	6.2	6.0	5.8	5.7	6.1	5.9	5.8	5.6	5.9	5.8	5.7	5.5	5.8	5.6	5.5	5.4	5.3
3	3.99	3.9	10.0	6.3	6.1	6.0	5.9	6.2	6.1	6.0	5.9	6.0	5.9	5.8	5.7	5.9	5.8	5.7	5.6	5.5

