

屋内照明器具特性	
品番 (品名)	S L B 1 9 2 7 1 B
光源	L D A 7 L - D - G / S / Z 6 × 3 8 1 0 . 0 l m
管理番号	K 0 1 4 0 2 7 4 (0) D B 1
B Z 分類	B Z 8

器具効率		9 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束		4 0 %	室指数	照明率 (X 0 . 0 1) Z C M																		
下方光束		5 0 %																				
保守率		良	0 . 6 3	0 . 6	4 1	3 0	2 2	1 7	3 8	2 7	2 1	1 6	3 1	2 3	1 8	1 4	2 6	1 9	1 5	1 1	7	
		中	0 . 6	0 . 8	4 8	3 7	3 0	2 4	4 4	3 4	2 7	2 2	3 7	2 9	2 4	1 9	3 0	2 4	2 0	1 6	1 0	
		否	0 . 5 6	1 . 0	5 4	4 3	3 5	2 9	4 9	4 0	3 3	2 7	4 1	3 4	2 8	2 4	3 4	2 8	2 3	2 0	1 3	
				1 . 2 5	5 9	4 8	4 1	3 5	5 4	4 5	3 8	3 3	4 5	3 8	3 3	2 8	3 7	3 2	2 7	2 4	1 6	
下方投影面積		c m ²		1 . 5	6 2	5 3	4 5	4 0	5 7	4 9	4 2	3 7	4 8	4 2	3 6	3 2	4 0	3 5	3 0	2 7	1 8	
等価発光面積		c m ²		2 . 0	6 7	5 9	5 2	4 7	6 2	5 5	4 9	4 4	5 2	4 7	4 2	3 8	4 3	3 9	3 5	3 2	2 2	
取付高さ	器具間隔最大限			2 . 5	7 1	6 3	5 7	5 2	6 5	5 9	5 3	4 8	5 5	5 0	4 6	4 2	4 6	4 2	3 8	3 5	2 5	
	横方向 (A)		縦方向 (B)	3 . 0	7 3	6 6	6 1	5 6	6 8	6 2	5 7	5 2	5 7	5 3	4 9	4 5	4 8	4 4	4 1	3 8	2 7	
H m	1 . 5 5 H m	1 . 2 9 H m	4 . 0	7 6	7 1	6 6	6 1	7 1	6 6	6 1	5 7	6 0	5 6	5 3	5 0	5 1	4 8	4 5	4 2	3 1		
			5 . 0	7 8	7 3	6 9	6 5	7 3	6 8	6 5	6 1	6 2	5 9	5 6	5 3	5 2	5 0	4 7	4 5	3 3		
			7 . 0	8 1	7 7	7 4	7 0	7 5	7 2	6 9	6 6	6 5	6 2	6 0	5 7	5 5	5 3	5 1	4 9	3 6		
			1 0 . 0	8 3	8 0	7 7	7 5	7 7	7 5	7 2	7 0	6 7	6 5	6 3	6 1	5 7	5 5	5 4	5 2	3 9		

