

屋内照明器具特性	
品番 (品名)	SLB15180+SLK22012+SLK290
光源	L LD2421LCB1 ×1 500.0 l m
管理番号	K0192486 (1) DR 1
B Z 分類	BZ1

器具効率		5 7 %	反 射 率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %		
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %		
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %		
上方光束		5 7 %	室指数	照明率 (X 0 . 0 1)																		Z C M	
下方光束																							
保守率		良 中 否	0 . 6 7	0 . 6	5 1	4 9	4 7	4 6	5 1	4 9	4 7	4 6	5 0	4 8	4 7	4 6	5 0	4 8	4 7	4 6	4 5		
			0 . 6 3	0 . 8	5 4	5 2	5 0	4 9	5 4	5 1	5 0	4 9	5 3	5 1	5 0	4 9	5 2	5 1	4 9	4 9	4 8		
			0 . 5 6	1 . 0	5 6	5 4	5 2	5 1	5 5	5 3	5 2	5 1	5 4	5 3	5 2	5 1	5 4	5 2	5 1	5 0	5 0		
				1 . 2 5	5 7	5 5	5 4	5 3	5 7	5 5	5 4	5 3	5 6	5 4	5 3	5 2	5 5	5 4	5 3	5 2	5 1		
下方投影面積		c m ²	1 . 5	5 8	5 6	5 5	5 4	5 7	5 6	5 5	5 4	5 6	5 5	5 4	5 3	5 6	5 5	5 4	5 3	5 2			
等価発光面積			c m ²	2 . 0	5 9	5 8	5 7	5 6	5 8	5 7	5 6	5 5	5 7	5 6	5 6	5 5	5 6	5 6	5 5	5 4	5 3		
取付 高さ	器具間隔最大限			2 . 5	6 0	5 8	5 8	5 7	5 9	5 8	5 7	5 6	5 8	5 7	5 6	5 6	5 7	5 6	5 6	5 5	5 4		
	横方向 (A)		縦方向 (B)		3 . 0	6 0	5 9	5 8	5 8	5 9	5 9	5 8	5 7	5 8	5 8	5 7	5 7	5 7	5 6	5 6	5 5		
H m	0 . 3 4 H m	0 . 3 5 H m	4 . 0	6 1	6 0	5 9	5 9	6 0	5 9	5 9	5 8	5 9	5 8	5 8	5 7	5 8	5 7	5 7	5 7	5 5			
			5 . 0	6 1	6 0	6 0	5 9	6 0	6 0	5 9	5 9	5 9	5 9	5 8	5 8	5 8	5 8	5 7	5 7	5 6			
			7 . 0	6 1	6 1	6 0	6 0	6 1	6 0	6 0	6 0	5 9	5 9	5 9	5 9	5 8	5 8	5 8	5 8	5 6			
			1 0 . 0	6 2	6 1	6 1	6 1	6 1	6 1	6 0	6 0	6 0	5 9	5 9	5 9	5 9	5 8	5 8	5 8	5 7			

