

屋内照明器具特性

品番 (品名)

P A V 1 2 5 4 5 W W W P 4 0 + N T S 9 0 5 5 1

光源

L E D 4 0 0 0 _ 7 0 _ 1 9 1 5 × 1 1 9 1 5 . 0 l m

管理番号

K 0 1 7 9 7 1 9 (0) D R 1

B Z 分類

B Z 1

器具効率

1 0 0 %

上方光束

0 %

下方光束

1 0 0 %

天井
壁
床

8 0 %

7 0 %

5 0 %

3 0 %

0 %

7 0

5 0

3 0

1 0

7 0

5 0

3 0

1 0

7 0

5 0

3 0

1 0

0 %

1 0 %

1 0 %

1 0 %

1 0 %

1 0 %

1 0 %

1 0 %

1 0 %

0 %

室指数

照明率 (× 0 . 0 1)

Z C M

保守率

良 0 . 6 3

中 0 . 6

否 0 . 5 6

下方投影面積

c m²

等価発光面積

c m²

取付

器具間隔最大限

高さ

横方向 (A)

縦方向 (B)

H m

0 . 5 1 H m

0 . 8 5 H m

0 . 6	7 6	6 8	6 3	6 0	7 5	6 8	6 3	6 0	7 4	6 7	6 3	6 0	7 2	6 7	6 3	6 0	5 8
0 . 8	8 4	7 7	7 3	6 9	8 3	7 7	7 2	6 9	8 1	7 6	7 2	6 9	8 0	7 5	7 1	6 9	6 7
1 . 0	8 9	8 3	7 9	7 5	8 8	8 2	7 8	7 5	8 6	8 1	7 8	7 5	8 4	8 0	7 7	7 4	7 3
1 . 2 5	9 3	8 8	8 4	8 1	9 2	8 7	8 3	8 0	9 0	8 6	8 3	8 0	8 8	8 5	8 2	7 9	7 8
1 . 5	9 6	9 1	8 7	8 4	9 5	9 0	8 7	8 4	9 3	8 9	8 6	8 4	9 1	8 8	8 5	8 3	8 1
2 . 0	9 9	9 5	9 2	9 0	9 8	9 4	9 2	8 9	9 6	9 3	9 0	8 8	9 4	9 1	8 9	8 7	8 6
2 . 5	1 0 1	9 8	9 5	9 3	1 0 0	9 7	9 4	9 2	9 8	9 5	9 3	9 1	9 6	9 4	9 2	9 0	8 8
3 . 0	1 0 2	1 0 0	9 7	9 5	1 0 1	9 9	9 6	9 5	9 9	9 7	9 5	9 3	9 7	9 5	9 4	9 2	9 0
4 . 0	1 0 4	1 0 2	1 0 0	9 8	1 0 3	1 0 1	9 9	9 8	1 0 0	9 9	9 7	9 6	9 8	9 7	9 6	9 5	9 3
5 . 0	1 0 5	1 0 3	1 0 2	1 0 0	1 0 4	1 0 2	1 0 1	9 9	1 0 1	1 0 0	9 9	9 8	9 9	9 8	9 7	9 6	9 4
7 . 0	1 0 6	1 0 5	1 0 3	1 0 2	1 0 5	1 0 4	1 0 2	1 0 1	1 0 2	1 0 1	1 0 0	1 0 0	1 0 0	9 9	9 8	9 6	9 6
1 0 . 0	1 0 7	1 0 6	1 0 5	1 0 4	1 0 5	1 0 5	1 0 4	1 0 3	1 0 3	1 0 3	1 0 2	1 0 1	1 0 1	1 0 1	1 0 0	1 0 0	9 7

配光曲線

ランプ光束1000lm

— 管軸に垂直 (A)
--- 管軸に平行 (B)

直射水平面照度

ランプ光束1000lm

8 0 lx X 1 0

H = 1 . 5

H = 2

H = 2 . 5

H = 3

H = 4

H = 5

A

A'

A

A'