

屋内照明器具特性	
品番 (品名)	SLB15180+SLK22014+SLK290
光源	LLD3401LCB1 ×1 700.0 lm
管理番号	K0193057 (0) DB1
BZ分類	BZ6

器具効率		81 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
					床	10 %				10 %				10 %				10 %				0 %
						室指数	照明率 (X0.01) Z CM															
保守率		良 中 否	0.63	0.6	41	31	25	20	38	29	24	20	34	27	22	18	30	24	20	17	13	
			0.6	0.8	48	38	31	27	45	36	30	26	40	33	28	24	35	29	25	22	18	
			0.56	1.0	52	43	37	32	49	41	35	30	44	37	32	28	38	33	29	26	21	
				1.25	57	48	42	37	53	46	40	35	47	41	36	32	42	37	33	29	24	
下方投影面積		cm ²	1.56	1.5	60	52	46	41	56	49	44	39	50	44	40	36	44	39	36	33	27	
等価発光面積				cm ²	2.0	64	57	52	47	61	54	49	45	54	49	45	41	48	44	40	37	31
取付 高さ	器具間隔最大限				2.5	67	61	56	51	63	58	53	49	56	52	48	45	50	46	43	41	34
	横方向 (A)		縦方向 (B)		3.0	69	64	59	55	65	60	56	52	58	54	51	48	52	49	46	43	36
H m	0.98 H m	0.98 H m		4.0	72	67	63	60	68	64	60	57	61	58	55	52	54	52	49	47	39	
				5.0	73	70	66	63	70	66	63	60	62	60	57	55	56	54	51	50	41	
				7.0	75	72	70	67	72	69	66	64	65	62	60	58	58	56	54	53	44	
				10.0	77	75	73	71	73	71	69	67	66	65	63	61	59	58	57	56	47	

