

屋内照明器具特性	
品番 (品名)	SLB15180+SLK22014+SLK290
光源	LLD2411LCB1 ×1 500.0 lm
管理番号	K0193061 (0) DB 1
BZ分類	BZ4/0.7/BZ5/3.5/BZ6

器具効率		8 9 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束		2 6 %	室指数	照明率 (X 0 . 0 1)																		Z C M
下方光束		6 3 %																				
保守率		良 中 否	0 . 6 3	0 . 6	4 8	3 8	3 2	2 7	4 6	3 7	3 1	2 7	4 1	3 4	2 9	2 5	3 7	3 1	2 7	2 4	2 0	
			0 . 6	0 . 8	5 5	4 6	3 9	3 4	5 3	4 4	3 8	3 3	4 7	4 0	3 5	3 1	4 3	3 7	3 2	2 9	2 5	
			0 . 5 6	1 . 0	6 0	5 1	4 5	4 0	5 7	4 9	4 3	3 8	5 1	4 5	4 0	3 6	4 6	4 1	3 7	3 3	2 8	
				1 . 2 5	6 5	5 6	5 0	4 5	6 2	5 4	4 8	4 3	5 5	4 9	4 4	4 0	5 0	4 5	4 1	3 7	3 2	
下方投影面積		c m ²		1 . 5	6 8	6 0	5 4	4 9	6 5	5 8	5 2	4 7	5 8	5 2	4 8	4 4	5 2	4 8	4 4	4 1	3 5	
等価発光面積			c m ²	2 . 0	7 3	6 6	6 0	5 6	6 9	6 3	5 8	5 4	6 2	5 7	5 3	5 0	5 6	5 2	4 9	4 6	3 9	
取付 高さ	器具間隔最大限			2 . 5	7 6	7 0	6 5	6 0	7 2	6 6	6 2	5 8	6 5	6 1	5 7	5 3	5 8	5 5	5 2	4 9	4 2	
	横方向 (A)			縦方向 (B)		3 . 0	7 8	7 2	6 8	6 4	7 4	6 9	6 5	6 1	6 7	6 3	5 9	5 6	6 0	5 7	5 4	5 2
H m	0 . 6 0 H m	0 . 6 0 H m	4 . 0	8 0	7 6	7 2	6 8	7 7	7 3	6 9	6 6	6 9	6 6	6 3	6 1	6 2	6 0	5 8	5 5	4 7		
			5 . 0	8 2	7 8	7 5	7 2	7 8	7 5	7 2	6 9	7 1	6 8	6 6	6 3	6 4	6 2	6 0	5 8	5 0		
			7 . 0	8 4	8 1	7 8	7 6	8 0	7 8	7 5	7 3	7 3	7 1	6 9	6 7	6 6	6 4	6 3	6 1	5 2		
			1 0 . 0	8 6	8 3	8 1	7 9	8 2	8 0	7 8	7 6	7 5	7 3	7 1	7 0	6 8	6 6	6 5	6 4	5 5		

