

屋内照明器具特性	
品番 (品名)	SLB15180+SLK22014+SLK290
光源	LLD2421LCB1 ×1 500.0 lm
管理番号	K0193062 (0) DB1
BZ分類	BZ4/0.7/BZ5/3.5/BZ6

器具効率		87 % 上方光束 25 % 下方光束 62 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) ZCM																
保守率		良 中 否	0.63	0.6	0.56	0.6	0.8	1.0	1.25	1.5	2.0	2.5	3.0	4.0	5.0	6.0	7.0	8.0	9.0	10.0	
			0.63	0.6	0.56	0.6	0.8	1.0	1.25	1.5	2.0	2.5	3.0	4.0	5.0	6.0	7.0	8.0	9.0	10.0	
			0.63	0.6	0.56	0.6	0.8	1.0	1.25	1.5	2.0	2.5	3.0	4.0	5.0	6.0	7.0	8.0	9.0	10.0	
			0.63	0.6	0.56	0.6	0.8	1.0	1.25	1.5	2.0	2.5	3.0	4.0	5.0	6.0	7.0	8.0	9.0	10.0	
下方投影面積		cm ²	1.25	1.5	2.0	2.5	3.0	4.0	5.0	6.0	7.0	8.0	9.0	10.0	12.0	15.0	20.0	25.0	30.0	40.0	
等価発光面積			1.5	2.0	2.5	3.0	4.0	5.0	6.0	7.0	8.0	9.0	10.0	12.0	15.0	20.0	25.0	30.0	40.0		
等価発光面積			2.0	2.5	3.0	4.0	5.0	6.0	7.0	8.0	9.0	10.0	12.0	15.0	20.0	25.0	30.0	40.0			
等価発光面積			2.5	3.0	4.0	5.0	6.0	7.0	8.0	9.0	10.0	12.0	15.0	20.0	25.0	30.0	40.0				
取付 高さ	器具間隔最大限		2.5	3.0	4.0	5.0	6.0	7.0	8.0	9.0	10.0	12.0	15.0	20.0	25.0	30.0	40.0	50.0	60.0	80.0	
	横方向 (A)		3.0	4.0	5.0	6.0	7.0	8.0	9.0	10.0	12.0	15.0	20.0	25.0	30.0	40.0	50.0	60.0	80.0		
H m	0.49 H m		4.0	5.0	6.0	7.0	8.0	9.0	10.0	12.0	15.0	20.0	25.0	30.0	40.0	50.0	60.0	80.0	100.0	150.0	
			5.0	6.0	7.0	8.0	9.0	10.0	12.0	15.0	20.0	25.0	30.0	40.0	50.0	60.0	80.0	100.0	150.0		
			7.0	8.0	9.0	10.0	12.0	15.0	20.0	25.0	30.0	40.0	50.0	60.0	80.0	100.0	150.0	200.0	300.0		
			10.0	12.0	15.0	20.0	25.0	30.0	40.0	50.0	60.0	80.0	100.0	150.0	200.0	300.0	400.0	600.0	1000.0		

