

屋内照明器具特性	
品番 (品名)	SLB15180+SLK22014+SLK290
光源	LLD3411LCB1 ×1 700.0 lm
管理番号	K0193690 (0) DB1
BZ分類	BZ1/0.9/BZ2/1.8/BZ3/6.0/BZ4

器具効率		9 2 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
				室指数	照明率 (X 0 . 0 1)																Z C M
保守率		良 中 否	0 . 6 3	0 . 6	6 4	5 6	5 1	4 8	6 3	5 6	5 1	4 7	6 0	5 4	5 0	4 7	5 8	5 3	4 9	4 6	4 4
			0 . 6	0 . 8	7 0	6 3	5 8	5 4	6 9	6 2	5 7	5 4	6 6	6 0	5 6	5 3	6 3	5 8	5 4	5 2	4 9
			0 . 5 6	1 . 0	7 5	6 8	6 2	5 9	7 3	6 6	6 2	5 8	6 9	6 4	6 0	5 7	6 6	6 2	5 8	5 6	5 3
				1 . 2 5	7 8	7 2	6 7	6 3	7 6	7 0	6 6	6 2	7 3	6 8	6 4	6 1	6 9	6 5	6 2	6 0	5 6
下方投影面積		c m ²	1 . 5	8 1	7 5	7 0	6 7	7 9	7 3	6 9	6 6	7 5	7 1	6 7	6 4	7 2	6 8	6 5	6 2	5 9	
			等価発光面積	2 . 0	8 4	7 9	7 5	7 2	8 2	7 8	7 4	7 1	7 8	7 4	7 1	6 9	7 5	7 1	6 9	6 7	6 3
取付 高さ	器具間隔最大限		2 . 5	8 6	8 2	7 8	7 5	8 4	8 0	7 7	7 4	8 0	7 7	7 4	7 2	7 6	7 4	7 1	6 9	6 5	
	横方向 (A) 縦方向 (B)		3 . 0	8 8	8 4	8 1	7 8	8 6	8 2	7 9	7 7	8 2	7 9	7 6	7 4	7 8	7 6	7 3	7 2	6 7	
H m	0 . 8 2 H m 0 . 8 7 H m		4 . 0	9 0	8 7	8 4	8 2	8 8	8 5	8 2	8 0	8 4	8 1	7 9	7 7	8 0	7 8	7 6	7 5	7 0	
			5 . 0	9 1	8 9	8 6	8 4	8 9	8 7	8 4	8 2	8 5	8 3	8 1	7 9	8 1	7 9	7 8	7 6	7 2	
			7 . 0	9 3	9 1	8 9	8 7	9 1	8 9	8 7	8 5	8 6	8 5	8 3	8 2	8 2	8 1	8 0	7 9	7 4	
			1 0 . 0	9 4	9 2	9 1	9 0	9 2	9 0	8 9	8 8	8 7	8 6	8 5	8 4	8 3	8 3	8 2	8 1	7 6	

