

屋内照明器具特性	
品番 (品名)	SLB15180+SLK22014+SLK290
光源	LLD2401LCB1 ×1 500.0 lm
管理番号	K0192484 (1) DR 1
BZ分類	BZ1

器具効率		39 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) Z CM																
保守率		良 中 否	0.67	0.6	32	29	28	27	32	29	28	27	31	29	28	27	31	29	27	27	26
			0.63	0.8	34	32	31	30	34	32	31	30	34	32	31	30	33	31	30	29	29
			0.56	1.0	36	34	33	32	36	34	33	32	35	34	32	32	34	33	32	31	31
			1.25	37	36	34	33	37	35	34	33	36	35	34	33	36	34	34	33	32	
下方投影面積		cm ²	1.5	38	37	35	35	38	36	35	34	37	36	35	34	36	35	35	34	33	
			2.0	39	38	37	36	39	38	37	36	38	37	36	36	37	36	36	35	35	
取付 高さ	器具間隔最大限		2.5	40	39	38	37	39	38	38	37	38	38	37	36	38	37	37	36	35	
	横方向 (A) 縦方向 (B)		3.0	40	39	38	38	40	39	38	38	39	38	38	37	38	38	37	37	36	
H m	0.87 H m 0.86 H m		4.0	41	40	39	39	40	39	39	38	39	39	38	38	39	38	38	37	37	
			5.0	41	40	40	39	40	40	39	39	40	39	39	38	39	38	38	38	37	
			7.0	41	41	40	40	41	40	40	40	40	40	39	39	39	39	39	38	37	
			10.0	41	41	41	41	41	41	40	40	40	40	40	40	39	39	39	39	38	

