

屋内照明器具特性	
品番 (品名)	SLB15181+SLK22000+SLK290
光源	LLD2421LCB1 ×1 500.0 lm
管理番号	K0193062 (0) DB 1
BZ分類	BZ4/0.7/BZ5/3.5/BZ6

器具効率		8 7 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
上方光束 下方光束		2 5 % 6 2 %	室指数	照明率 (X 0 . 0 1) Z C M																	
保守率		良 中 否	0 . 6 3	0 . 6	4 7	3 7	3 1	2 7	4 5	3 6	3 0	2 6	4 0	3 3	2 8	2 4	3 6	3 0	2 6	2 3	2 0
			0 . 6	0 . 8	5 4	4 4	3 8	3 3	5 1	4 3	3 7	3 2	4 6	3 9	3 4	3 0	4 1	3 6	3 1	2 8	2 4
			0 . 5 6	1 . 0	5 9	5 0	4 3	3 8	5 6	4 8	4 2	3 7	5 0	4 3	3 8	3 5	4 5	4 0	3 5	3 2	2 7
			1 . 2 5	6 3	5 5	4 8	4 4	6 0	5 2	4 7	4 2	5 4	4 8	4 3	3 9	4 8	4 3	3 9	3 6	3 1	
下方投影面積		c m ²	1 . 5	6 7	5 9	5 3	4 8	6 3	5 6	5 1	4 6	5 7	5 1	4 7	4 3	5 1	4 6	4 3	3 9	3 4	
等価発光面積			c m ²	2 . 0	7 1	6 4	5 9	5 4	6 7	6 1	5 6	5 2	6 1	5 6	5 2	4 8	5 4	5 1	4 7	4 4	3 8
取付	器具間隔最大限		2 . 5	7 4	6 8	6 3	5 9	7 0	6 5	6 0	5 6	6 3	5 9	5 5	5 2	5 7	5 3	5 0	4 8	4 1	
高さ	横方向 (A) 縦方向 (B)		3 . 0	7 6	7 1	6 6	6 2	7 2	6 7	6 3	6 0	6 5	6 1	5 8	5 5	5 9	5 6	5 3	5 0	4 3	
H m	0 . 4 9 H m 0 . 4 9 H m		4 . 0	7 9	7 4	7 0	6 7	7 5	7 1	6 7	6 4	6 8	6 5	6 2	5 9	6 1	5 8	5 6	5 4	4 6	
			5 . 0	8 0	7 6	7 3	7 0	7 6	7 3	7 0	6 7	6 9	6 7	6 4	6 2	6 3	6 0	5 8	5 7	4 8	
			7 . 0	8 2	7 9	7 7	7 4	7 8	7 6	7 3	7 1	7 1	6 9	6 7	6 5	6 4	6 3	6 1	6 0	5 1	
			1 0 . 0	8 4	8 2	8 0	7 8	8 0	7 8	7 6	7 4	7 3	7 1	7 0	6 8	6 6	6 5	6 4	6 2	5 4	

