

屋内照明器具特性	
品番 (品名)	S L B 7 1 5 3 1 W
光源	LDA5 L - D - G - E 1 7 / S / Z 4 × 1 4 4 0 . 0 l m
管理番号	K 0 1 2 8 4 9 2 (0) D B 1
B Z 分類	B Z 7

器具効率		8 4 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束 下方光束		3 3 % 5 1 %	室指数	照明率 (X 0 . 0 1) Z C M																		
保守率		良 中 否	0 . 6 3	0 . 6	0 . 6	3 9	2 9	2 2	1 7	3 6	2 7	2 1	1 6	3 1	2 3	1 8	1 4	2 6	2 0	1 6	1 3	9
			0 . 6	0 . 8	4 6	3 6	2 9	2 4	4 3	3 4	2 7	2 3	3 7	2 9	2 4	2 0	3 1	2 5	2 1	1 7	1 3	
			0 . 5 6	1 . 0	5 1	4 1	3 4	2 9	4 8	3 9	3 2	2 7	4 1	3 4	2 8	2 4	3 5	2 9	2 5	2 1	1 6	
				1 . 2 5	5 6	4 7	4 0	3 4	5 2	4 4	3 7	3 2	4 5	3 8	3 3	2 9	3 8	3 3	2 9	2 5	1 9	
下方投影面積		cm ²	1 . 5	5 9	5 1	4 4	3 9	5 5	4 7	4 1	3 6	4 7	4 1	3 6	3 2	4 0	3 6	3 2	2 8	2 1		
等価発光面積		cm ²	2 . 0	6 4	5 6	5 0	4 5	6 0	5 3	4 7	4 3	5 2	4 6	4 2	3 8	4 4	4 0	3 6	3 3	2 5		
取付 高さ	器具間隔最大限		2 . 5	6 7	6 0	5 5	5 0	6 3	5 7	5 2	4 7	5 4	5 0	4 5	4 2	4 6	4 3	3 9	3 7	2 8		
	横方向 (A) 縦方向 (B)		3 . 0	6 9	6 3	5 8	5 4	6 5	5 9	5 5	5 1	5 6	5 2	4 8	4 5	4 8	4 5	4 2	3 9	3 0		
H m	1 . 4 2 H m	1 . 4 3 H m	4 . 0	7 2	6 7	6 3	5 9	6 8	6 3	5 9	5 6	5 9	5 5	5 2	4 9	5 1	4 8	4 6	4 3	3 4		
			5 . 0	7 4	7 0	6 6	6 2	7 0	6 6	6 2	5 9	6 1	5 8	5 5	5 2	5 3	5 0	4 8	4 6	3 6		
			7 . 0	7 6	7 3	7 0	6 7	7 2	6 9	6 6	6 3	6 3	6 1	5 8	5 6	5 5	5 3	5 1	4 9	3 9		
			1 0 . 0	7 8	7 6	7 3	7 1	7 4	7 1	6 9	6 7	6 5	6 3	6 1	6 0	5 7	5 5	5 4	5 2	4 2		

