

屋内照明器具特性

品番 (品名)	XF X4 5 0 UKN									
光源	LED5000_85_4470 x1 4470.0 lm									
管理番号	K0193734(1)D 1									
BZ分類	BZ4/0.9/BZ3									

器具効率	100%	天井	80%				70%				50%				30%				0%		
	上方光束		0%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		100%		床	10%				10%				10%				10%			
室指数	照明率 (X0.01) ZCM																				
保守率	良	0.81	0.6	61	49	42	37	59	49	42	37	57	48	41	37	55	47	41	37	35	
	中	0.77	0.8	71	60	53	48	69	60	53	48	67	58	52	48	65	57	52	47	45	
	否	0.68	1.0	77	68	61	56	76	67	61	56	73	66	60	55	71	64	59	55	53	
			1.25	83	75	68	63	82	74	68	63	79	72	67	63	76	71	66	62	60	
下方投影面積			1.5	87	79	74	69	86	78	73	68	83	77	72	68	80	75	71	67	65	
			2.0	92	86	81	77	91	85	80	76	88	83	79	75	85	81	78	74	72	
取付高さ	器具間隔最大限		2.5	95	90	86	82	94	89	85	81	91	87	83	80	88	85	82	79	77	
	横方向 (A)	縦方向 (B)	3.0	98	93	89	86	96	92	88	85	93	90	87	84	91	88	85	83	80	
1.5m	1.9m	2.04m	4.0	100	97	94	91	99	96	93	90	96	93	91	89	94	91	89	87	85	
2	2.51	2.59	5.0	102	99	96	94	100	98	95	93	98	96	93	92	95	93	92	90	87	
2.5	3.13	3.15	7.0	104	102	100	98	102	100	98	97	100	98	97	95	97	96	95	93	91	
3	3.74	3.72	10.0	105	104	102	101	104	102	101	100	101	100	99	98	99	98	97	96	93	

