

屋内照明器具特性	
品番 (品名)	XF X430 WE W
光源	LED4000_85_2950 ×1 2950.0 lm
管理番号	K0192166 (0) DR 1
BZ分類	BZ5/3.5/BZ6/4.5/BZ5/6.0/BZ6

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %					
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %					
				床	10 %				10 %				10 %				10 %				0 %					
上方光束		10 %	室指数	照明率 (X0.01)																			Z	C		M
下方光束		90 %																								
保守率		良 中 否	0.83	0.6	54	41	34	28	52	40	33	28	49	39	32	27	45	37	31	26	24					
			0.81	0.8	63	51	43	37	61	50	43	37	57	48	41	36	54	46	40	35	32					
			0.77	1.0	70	58	50	44	67	57	49	44	63	54	48	42	59	52	46	41	38					
				1.25	75	65	57	51	73	63	56	50	68	60	54	49	64	57	52	48	44					
下方投影面積		cm ²	1.5	79	70	62	57	77	68	61	56	72	65	59	54	68	62	56	52	48						
			2.0	85	77	70	65	82	75	69	63	77	71	66	61	73	68	63	59	55						
等価発光面積	cm ²	2.5	89	81	75	70	86	79	74	69	81	75	71	67	76	72	68	64	60							
		3.0	91	85	79	74	88	83	78	73	83	79	74	71	79	75	71	68	63							
1.5m	1.94 m	2.1 m	4.0	94	89	84	80	92	87	83	79	87	83	79	76	82	79	76	73	68						
2	2.57	2.64	5.0	96	92	88	84	94	90	86	83	89	86	82	80	84	81	79	77	71						
2.5	3.19	3.2	7.0	99	95	92	89	96	93	90	88	91	89	86	84	87	85	83	81	75						
3	3.81	3.78	10.0	101	98	96	93	98	96	94	92	94	92	90	88	89	87	86	84	79						

