

屋内照明器具特性	
品番 (品名)	SLB15181+SLK22008+SLK290
光源	LLD2411LCB1 ×1 500.0 lm
管理番号	K0193688 (0) DB1
BZ分類	BZ1/0.9/BZ2/2.3/BZ3/8.5/BZ4

器具効率		9 2 % 上方光束 9 % 下方光束 8 3 %	反射率	天井	8 0 %					7 0 %					5 0 %					3 0 %					0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %				
				床	1 0 %					1 0 %					1 0 %					1 0 %					0 %
				室指数	照明率 (X 0 . 0 1) Z C M																				
保守率		良 中 否	0 . 6 3	0 . 6	0 . 5 6	0 . 6	6 5	5 7	5 2	4 9	6 4	5 7	5 2	4 8	6 1	5 5	5 1	4 8	5 9	5 4	5 0	4 7	4 5		
			0 . 6	0 . 8	7 1	6 4	5 9	5 5	7 0	6 3	5 8	5 5	6 7	6 1	5 7	5 4	6 4	5 9	5 6	5 3	5 0				
			0 . 5 6	1 . 0	7 5	6 8	6 3	6 0	7 4	6 7	6 3	5 9	7 0	6 5	6 1	5 8	6 7	6 3	5 9	5 7	5 4				
			1 . 2 5	7 9	7 3	6 8	6 4	7 7	7 1	6 7	6 3	7 4	6 9	6 5	6 2	7 0	6 6	6 3	6 1	5 8					
下方投影面積		c m ²	1 . 5	8 2	7 6	7 1	6 8	8 0	7 4	7 0	6 7	7 6	7 2	6 8	6 5	7 3	6 9	6 6	6 3	6 1	6 0				
等価発光面積			c m ²	2 . 0	8 5	8 0	7 6	7 3	8 3	7 9	7 5	7 2	7 9	7 5	7 2	7 0	7 6	7 2	7 0	6 8	6 4				
取付高さ				器具間隔最大限		2 . 5	8 7	8 3	7 9	7 6	8 5	8 1	7 8	7 5	8 1	7 8	7 5	7 3	7 7	7 5	7 2	7 0	6 6		
横方向 (A)		縦方向 (B)		3 . 0	8 9	8 5	8 2	7 9	8 7	8 3	8 0	7 8	8 3	8 0	7 7	7 5	7 9	7 7	7 4	7 3	6 8				
H m	0 . 8 2 H m	0 . 8 6 H m	4 . 0	9 1	8 8	8 5	8 2	8 9	8 6	8 3	8 1	8 5	8 2	8 0	7 8	8 1	7 9	7 7	7 6	7 1					
			5 . 0	9 2	8 9	8 7	8 5	9 0	8 8	8 5	8 3	8 6	8 4	8 2	8 0	8 2	8 0	7 9	7 7	7 3					
			7 . 0	9 4	9 2	9 0	8 8	9 1	9 0	8 8	8 6	8 7	8 6	8 4	8 3	8 3	8 2	8 1	8 0	7 5					
			1 0 . 0	9 5	9 3	9 2	9 0	9 3	9 1	9 0	8 9	8 8	8 7	8 6	8 5	8 4	8 4	8 3	8 2	7 7					

