

屋内照明器具特性

品番 (品名)	XF X4 3 7 GE V	
光源	LED3500_85_2970 x1	2970.0 lm
管理番号	K0192146(0)D 1	
BZ分類	BZ4	

器具効率	100%	天井	80%				70%				50%				30%				0%	
	上方光束 0%		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	100%	床		10%				10%				10%				10%				0%
室指数	照明率 (X0.01)																			ZCM
保守率	良	0.81	0.6	5.9	4.8	4.0	3.5	5.8	4.7	4.0	3.5	5.6	4.6	4.0	3.5	5.4	4.5	3.9	3.5	3.3
	中	0.77	0.8	7.0	5.9	5.2	4.7	6.8	5.8	5.1	4.6	6.6	5.7	5.1	4.6	6.4	5.6	5.0	4.6	4.4
	否	0.68	1.0	7.7	6.7	6.0	5.5	7.5	6.6	6.0	5.4	7.3	6.5	5.9	5.4	7.0	6.3	5.8	5.4	5.2
			1.25	8.3	7.4	6.8	6.2	8.1	7.3	6.7	6.2	7.8	7.1	6.6	6.2	7.6	7.0	6.5	6.1	5.9
下方投影面積	c m ²		1.5	8.7	7.9	7.3	6.8	8.5	7.8	7.2	6.8	8.2	7.6	7.1	6.7	8.0	7.5	7.0	6.7	6.4
	等価発光面積		c m ²	2.0	9.2	8.6	8.0	7.6	9.1	8.5	8.0	7.6	8.8	8.3	7.8	7.5	8.5	8.1	7.7	7.4
取付高さ	器具間隔最大限		2.5	9.5	9.0	8.5	8.1	9.4	8.9	8.5	8.1	9.1	8.7	8.3	8.0	8.8	8.5	8.2	7.9	7.7
	横方向 (A)	縦方向 (B)	3.0	9.7	9.3	8.9	8.5	9.6	9.2	8.8	8.5	9.3	9.0	8.6	8.4	9.1	8.8	8.5	8.3	8.0
1.5m	1.9m	2.12m	4.0	10.0	9.7	9.3	9.0	9.9	9.5	9.2	9.0	9.6	9.3	9.1	8.8	9.4	9.1	8.9	8.7	8.5
2	2.52	2.66	5.0	10.2	9.9	9.6	9.4	10.0	9.8	9.5	9.3	9.8	9.6	9.3	9.1	9.5	9.4	9.2	9.0	8.7
2.5	3.13	3.23	7.0	10.4	10.1	9.9	9.8	10.2	10.0	9.8	9.7	10.0	9.8	9.7	9.5	9.7	9.6	9.5	9.3	9.1
3	3.74	3.81	10.0	10.5	10.4	10.2	10.1	10.4	10.2	10.1	10.0	10.1	10.0	9.9	9.8	9.9	9.8	9.7	9.6	9.3

