

屋内照明器具特性

品番 (品名)	XLGB1070														
光源	LLD2000CU1 x1 566.0 lm														
管理番号	K0190104(1)DR1														
BZ分類	BZ3														

器具効率	72%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束 下方光束	1% 71%	室指数	照明率 (X0.01) ZCM																		
保守率	良 中 否 0.67 0.63 0.56	0.6	46	38	33	30	45	38	33	30	43	37	33	30	42	36	32	30	28		
		0.8	53	46	42	38	52	46	41	38	50	45	41	38	49	44	40	38	36		
		1.0	58	52	47	44	57	51	47	44	55	50	46	43	53	49	46	43	42		
		1.25	61	56	52	49	60	55	52	49	59	54	51	48	57	53	50	48	46		
下方投影面積 等価発光面積	c m ² c m ²	1.5	64	59	55	52	63	58	55	52	61	57	54	52	59	56	53	51	50		
		2.0	67	63	60	57	66	62	59	57	64	61	59	56	62	60	58	56	54		
取付 高さ	器具間隔最大限		2.5	69	66	63	61	68	65	62	60	66	64	61	59	64	62	60	59	57	
	横方向 (A) H m	縦方向 (B) H m	3.0	71	68	65	63	70	67	64	62	68	65	63	62	66	64	62	61	59	
H m	1.33H m	1.33H m	4.0	72	70	68	66	71	69	67	66	69	68	66	65	68	66	65	64	62	
			5.0	73	71	70	68	72	71	69	68	70	69	68	66	69	67	66	65	63	
			7.0	74	73	72	70	73	72	71	70	72	71	70	69	70	69	68	67	65	
			10.0	75	74	73	72	74	73	73	72	73	72	71	70	71	70	70	69	67	

