

| 屋内照明器具特性 |                             |
|----------|-----------------------------|
| 品番 (品名)  | SLB15181+SLK22011+SLK290    |
| 光源       | L LD2421LCB1 ×1 500.0 l m   |
| 管理番号     | K0193682 ( 0 ) DB 1         |
| B Z 分類   | BZ1 / 1.4 / BZ2 / 4.5 / BZ3 |

| 器具効率     |           | 97 %             | 天井               | 80 %          |    |      |    | 70 % |    |      |    | 50 % |    |      |    | 30 % |    |      |    | 0 %   |     |
|----------|-----------|------------------|------------------|---------------|----|------|----|------|----|------|----|------|----|------|----|------|----|------|----|-------|-----|
|          |           |                  |                  | 壁             | 70 | 50   | 30 | 10   | 70 | 50   | 30 | 10   | 70 | 50   | 30 | 10   | 70 | 50   | 30 | 10    | 0 % |
|          |           |                  |                  |               | 床  | 10 % |    |      |    | 10 % |    |      |    | 10 % |    |      |    | 10 % |    |       |     |
| 上方光束     |           | 12 %             | 室指数              | 照明率 ( X0.01 ) |    |      |    |      |    |      |    |      |    |      |    |      |    |      |    | Z C M |     |
| 下方光束     |           | 85 %             |                  |               |    |      |    |      |    |      |    |      |    |      |    |      |    |      |    |       |     |
| 保守率      |           | 良<br>中<br>否      | 0.63             | 0.6           | 69 | 61   | 56 | 53   | 68 | 60   | 56 | 52   | 65 | 59   | 55 | 52   | 62 | 57   | 54 | 51    | 49  |
|          |           |                  | 0.6              | 0.8           | 76 | 68   | 63 | 60   | 74 | 67   | 63 | 59   | 71 | 65   | 61 | 58   | 68 | 63   | 60 | 57    | 55  |
|          |           |                  | 0.56             | 1.0           | 80 | 73   | 68 | 65   | 78 | 72   | 68 | 64   | 75 | 70   | 66 | 63   | 72 | 67   | 64 | 61    | 59  |
|          |           |                  |                  | 1.25          | 84 | 78   | 73 | 69   | 82 | 76   | 72 | 69   | 78 | 74   | 70 | 67   | 75 | 71   | 68 | 65    | 62  |
| 下方投影面積   |           | c m <sup>2</sup> | 1.5              | 87            | 81 | 77   | 73 | 85   | 79 | 75   | 72 | 81   | 76 | 73   | 70 | 77   | 73 | 71   | 68 | 65    |     |
| 等価発光面積   |           |                  | c m <sup>2</sup> | 2.0           | 90 | 85   | 81 | 78   | 88 | 84   | 80 | 77   | 84 | 80   | 77 | 75   | 80 | 77   | 75 | 72    | 68  |
| 取付<br>高さ | 器具間隔最大限   |                  | 2.5              | 92            | 88 | 85   | 82 | 90   | 86 | 83   | 80 | 86   | 83 | 80   | 78 | 82   | 79 | 77   | 75 | 71    |     |
|          | 横方向 ( A ) |                  | 縦方向 ( B )        | 3.0           | 94 | 90   | 87 | 84   | 91 | 88   | 85 | 83   | 87 | 84   | 82 | 80   | 83 | 81   | 79 | 77    | 73  |
| H m      | 0.53 H m  | 0.53 H m         | 4.0              | 96            | 93 | 90   | 88 | 93   | 91 | 88   | 86 | 89   | 87 | 85   | 83 | 85   | 83 | 81   | 80 | 75    |     |
|          |           |                  | 5.0              | 97            | 94 | 92   | 90 | 94   | 92 | 90   | 88 | 90   | 88 | 86   | 85 | 86   | 84 | 83   | 82 | 77    |     |
|          |           |                  | 7.0              | 98            | 96 | 95   | 93 | 96   | 94 | 93   | 91 | 91   | 90 | 89   | 87 | 87   | 86 | 85   | 84 | 79    |     |
|          |           |                  | 10.0             | 99            | 98 | 97   | 95 | 97   | 96 | 94   | 93 | 92   | 91 | 90   | 89 | 88   | 87 | 87   | 86 | 80    |     |

