

# 屋内照明器具特性

|         |   |  |  |  |  |
|---------|---|--|--|--|--|
| 品番 (品名) | XLGB1416                                |  |  |  |  |
| 光源      | LLD3000CU1 x1 795.0 lm                  |  |  |  |  |
| 管理番号    | K0182745(0)DB1                          |  |  |  |  |
| BZ分類    | BZ4/0.7/BZ3/2.8/BZ2/4.5/BZ3<br>/6.0/BZ2 |  |  |  |  |

|        |         |                 |               |    |    |    |     |    |    |    |     |    |    |    |     |    |    |    |     |    |
|--------|---------|-----------------|---------------|----|----|----|-----|----|----|----|-----|----|----|----|-----|----|----|----|-----|----|
| 器具効率   | 73%     | 天井              | 80%           |    |    |    | 70% |    |    |    | 50% |    |    |    | 30% |    |    |    | 0%  |    |
|        |         | 壁               | 70            | 50 | 30 | 10 | 70  | 50 | 30 | 10 | 70  | 50 | 30 | 10 | 70  | 50 | 30 | 10 | 0%  |    |
| 上方光束   | 0%      | 床               | 10%           |    |    |    | 10% |    |    |    | 10% |    |    |    | 10% |    |    |    | 0%  |    |
| 下方光束   | 73%     | 室指数             | 照明率 ( X0.01 ) |    |    |    |     |    |    |    |     |    |    |    |     |    |    |    | ZCM |    |
| 保守率    | 良       | 0.67            | 0.6           | 45 | 37 | 32 | 28  | 44 | 37 | 32 | 28  | 43 | 36 | 31 | 28  | 41 | 35 | 31 | 28  | 27 |
|        | 中       | 0.63            | 0.8           | 53 | 46 | 41 | 38  | 52 | 46 | 41 | 38  | 51 | 45 | 41 | 37  | 49 | 44 | 40 | 37  | 36 |
|        | 否       | 0.56            | 1.0           | 59 | 52 | 48 | 44  | 58 | 52 | 47 | 44  | 56 | 51 | 47 | 44  | 54 | 50 | 46 | 44  | 42 |
|        |         |                 | 1.25          | 63 | 57 | 53 | 50  | 62 | 57 | 53 | 50  | 60 | 56 | 52 | 49  | 58 | 55 | 52 | 49  | 48 |
| 下方投影面積 |         | cm <sup>2</sup> | 1.5           | 66 | 61 | 57 | 54  | 65 | 60 | 57 | 54  | 63 | 59 | 56 | 53  | 61 | 58 | 55 | 53  | 51 |
| 等価発光面積 |         | cm <sup>2</sup> | 2.0           | 69 | 65 | 62 | 59  | 68 | 65 | 62 | 59  | 66 | 63 | 61 | 58  | 65 | 62 | 60 | 58  | 56 |
| 取付高さ   | 器具間隔最大限 |                 | 2.5           | 71 | 68 | 65 | 63  | 70 | 67 | 65 | 62  | 68 | 66 | 64 | 62  | 67 | 65 | 63 | 61  | 59 |
|        | 横方向 (A) | 縦方向 (B)         | 3.0           | 73 | 70 | 67 | 65  | 72 | 69 | 67 | 65  | 70 | 68 | 66 | 64  | 68 | 66 | 65 | 63  | 61 |
| Hm     | 1.22Hm  | 1.22Hm          | 4.0           | 74 | 72 | 70 | 68  | 73 | 71 | 70 | 68  | 72 | 70 | 68 | 67  | 70 | 68 | 67 | 66  | 64 |
|        |         |                 | 5.0           | 75 | 73 | 72 | 70  | 74 | 73 | 71 | 70  | 73 | 71 | 70 | 69  | 71 | 70 | 69 | 68  | 66 |
|        |         |                 | 7.0           | 76 | 75 | 74 | 73  | 75 | 74 | 73 | 72  | 74 | 73 | 72 | 71  | 72 | 71 | 70 | 70  | 68 |
|        |         |                 | 10.0          | 77 | 76 | 75 | 75  | 76 | 75 | 75 | 74  | 75 | 74 | 73 | 73  | 73 | 72 | 72 | 71  | 69 |

