

屋内照明器具特性

| | | | | | | | | | | |
|---------|------------------------------|--|--|--|--|--|--|--|--|--|
| 品番 (品名) | XF X4 6 0 P NN | | | | | | | | | |
| 光源 | LED5000_85_6500 x1 6500.0 lm | | | | | | | | | |
| 管理番号 | K0192926(0)DB1 | | | | | | | | | |
| BZ分類 | BZ5/1.4/BZ4 | | | | | | | | | |

| | | | | | | | | | | | | | | | | | | | | | | | |
|--------|------------------|---------|--------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|-----|----|-----|----|----|----|----|--|-----|
| 器具効率 | 100% | 天井 | 80% | | | | 70% | | | | 50% | | | | 30% | | | | 0% | | | | |
| | | | 反射率 | 壁 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 0% | | |
| | | | | 床 | 10% | | | | 10% | | | | 10% | | | | 10% | | | | 0% | | |
| 上方光束 | 0% | 室指数 | 照明率 (X0.01) | | | | | | | | | | | | | | | | | | | | ZCM |
| 下方光束 | 100% | | | | | | | | | | | | | | | | | | | | | | |
| 保守率 | 良 中 否 | 0.81 | 0.6 | 57 | 45 | 37 | 32 | 56 | 44 | 37 | 32 | 54 | 43 | 37 | 32 | 51 | 42 | 36 | 32 | 30 | | | |
| | | 0.77 | 0.8 | 67 | 56 | 48 | 42 | 66 | 55 | 48 | 42 | 63 | 54 | 47 | 42 | 61 | 53 | 47 | 42 | 40 | | | |
| | | 0.68 | 1.0 | 74 | 63 | 56 | 50 | 72 | 63 | 55 | 50 | 70 | 61 | 55 | 50 | 67 | 60 | 54 | 49 | 47 | | | |
| | | | 1.25 | 80 | 71 | 63 | 58 | 78 | 70 | 63 | 58 | 75 | 68 | 62 | 57 | 73 | 66 | 61 | 57 | 54 | | | |
| 下方投影面積 | c m ² | 1.5 | 84 | 76 | 69 | 64 | 83 | 75 | 68 | 63 | 80 | 73 | 67 | 63 | 77 | 71 | 66 | 62 | 60 | | | | |
| | | 2.0 | 90 | 83 | 77 | 72 | 88 | 82 | 76 | 72 | 85 | 80 | 75 | 71 | 83 | 78 | 74 | 70 | 68 | | | | |
| 取付高さ | 器具間隔最大限 | | 2.5 | 93 | 87 | 82 | 78 | 92 | 86 | 81 | 77 | 89 | 84 | 80 | 76 | 86 | 82 | 79 | 75 | 73 | | | |
| | 横方向 (A) | 縦方向 (B) | 3.0 | 96 | 91 | 86 | 82 | 94 | 90 | 85 | 82 | 91 | 87 | 84 | 80 | 89 | 85 | 82 | 79 | 77 | | | |
| 1.5m | 1.94 m | 2.13 m | 4.0 | 99 | 95 | 91 | 88 | 98 | 94 | 90 | 87 | 95 | 92 | 89 | 86 | 92 | 89 | 87 | 85 | 82 | | | |
| 2 | 2.57 | 2.69 | 5.0 | 101 | 97 | 94 | 92 | 99 | 96 | 93 | 91 | 97 | 94 | 92 | 89 | 94 | 92 | 90 | 88 | 85 | | | |
| 2.5 | 3.2 | 3.26 | 7.0 | 103 | 100 | 98 | 96 | 102 | 99 | 97 | 95 | 99 | 97 | 95 | 94 | 97 | 95 | 93 | 92 | 89 | | | |
| 3 | 3.82 | 3.85 | 10.0 | 105 | 103 | 101 | 99 | 103 | 102 | 100 | 99 | 101 | 99 | 98 | 97 | 98 | 97 | 96 | 95 | 92 | | | |

