

屋内照明器具特性

品番 (品名)	XLF213NTNC(JYOUJI_CEILIN)	
光源	LED5000_85_1550 ×1	1550.0 lm
管理番号	K0153232(4)DB1	
BZ分類	BZ6/0.7/BZ5/3.5/BZ6/4.5/BZ5/6.0/BZ6	

器具効率	100%	天井	80%				70%				50%				30%				0%			
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%			
上方光束	9%	床	10%				10%				10%				10%				0%			
下方光束	91%	室指数	照明率 (X0.01) ZCM																			
保守率	良 中 否	0.83	0.6	5.3	4.1	3.3	2.7	5.2	4.0	3.2	2.7	4.8	3.8	3.1	2.6	4.5	3.6	3.0	2.6	2.3		
		0.81	0.8	6.3	5.1	4.3	3.7	6.1	5.0	4.2	3.6	5.7	4.7	4.1	3.5	5.4	4.5	3.9	3.5	3.2		
		0.77	1.0	6.9	5.8	5.0	4.4	6.7	5.7	4.9	4.3	6.3	5.4	4.7	4.2	5.9	5.1	4.6	4.1	3.8		
			1.25	7.5	6.5	5.7	5.1	7.3	6.3	5.6	5.0	6.8	6.0	5.4	4.9	6.4	5.7	5.2	4.7	4.4		
下方投影面積		1.5	7.9	7.0	6.2	5.6	7.7	6.8	6.1	5.5	7.2	6.5	5.9	5.4	6.8	6.2	5.6	5.2	4.8			
等価発光面積		2.0	8.5	7.7	7.0	6.4	8.2	7.5	6.9	6.3	7.8	7.1	6.6	6.1	7.3	6.8	6.3	5.9	5.5			
取付高さ	器具間隔最大限		2.5	8.9	8.1	7.5	7.0	8.6	7.9	7.4	6.9	8.1	7.6	7.1	6.7	7.7	7.2	6.8	6.5	6.0		
	横方向 (A)	縦方向 (B)	3.0	9.1	8.5	7.9	7.4	8.9	8.3	7.8	7.3	8.4	7.9	7.5	7.1	7.9	7.5	7.2	6.8	6.4		
1.5m	1.94m	1.91m	4.0	9.4	8.9	8.5	8.0	9.2	8.7	8.3	7.9	8.7	8.3	8.0	7.6	8.3	8.0	7.7	7.4	6.9		
2	2.58	2.51	5.0	9.7	9.2	8.8	8.4	9.4	9.0	8.6	8.3	8.9	8.6	8.3	8.0	8.5	8.2	8.0	7.7	7.2		
2.5	3.23	3.11	7.0	9.9	9.6	9.2	8.9	9.7	9.4	9.1	8.8	9.2	8.9	8.7	8.5	8.8	8.6	8.4	8.2	7.7		
3	3.87	3.65	10.0	10.1	9.8	9.6	9.4	9.9	9.6	9.4	9.2	9.4	9.2	9.0	8.9	9.0	8.8	8.7	8.5	8.0		

