

屋内照明器具特性

品番 (品名)	XLGB1520				
光源	LLD3000CU1 x1		795.0 lm		
管理番号	K0179027(0)DR1				
BZ分類	BZ5				

器具効率	78%	天井	80%				70%				50%				30%				0%		
	上方光束		4%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		74%		床	10%				10%				10%				10%			
室指数	照明率 (X0.01)																			ZCM	
保守率	良	0.67	0.6	4.2	3.2	2.6	2.2	4.1	3.2	2.6	2.1	3.9	3.0	2.5	2.1	3.6	2.9	2.4	2.1	1.9	
	中	0.63	0.8	5.0	4.0	3.4	2.9	4.8	4.0	3.3	2.9	4.6	3.8	3.3	2.9	4.3	3.7	3.2	2.8	2.6	
	否	0.56	1.0	5.5	4.6	4.0	3.5	5.3	4.5	3.9	3.4	5.0	4.3	3.8	3.4	4.8	4.2	3.7	3.3	3.1	
			0.56	1.25	5.9	5.1	4.5	4.0	5.8	5.0	4.5	4.0	5.5	4.8	4.3	3.9	5.2	4.6	4.2	3.9	3.6
下方投影面積			c m ²																		
			c m ²																		
取付高さ	器具間隔最大限																				
	横方向 (A)	縦方向 (B)																			
H m	1.18 H m	1.18 H m	4.0	7.5	7.1	6.7	6.4	7.3	6.9	6.6	6.3	7.0	6.7	6.4	6.2	6.7	6.4	6.2	6.0	5.7	
			5.0	7.6	7.3	7.0	6.7	7.5	7.2	6.9	6.6	7.1	6.9	6.7	6.4	6.9	6.6	6.4	6.3	5.9	
			7.0	7.8	7.6	7.3	7.1	7.6	7.4	7.2	7.0	7.3	7.2	7.0	6.8	7.1	6.9	6.8	6.6	6.3	
			10.0	8.0	7.8	7.6	7.4	7.8	7.6	7.5	7.3	7.5	7.4	7.2	7.1	7.2	7.1	7.0	6.9	6.6	

