

屋内照明器具特性	
品番 (品名)	XLGB1521
光源	LLD3000CU1 x1 795.0 lm
管理番号	K0178766(0)DR1
BZ分類	BZ1/1.1/BZ2

器具効率	60%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	1%	床	10%				10%				10%				10%				0%	
下方光束	59%	室指数	照明率 (X0.01)																ZCM	
保守率	良	0.67	0.6	43	38	34	32	42	37	34	32	41	37	34	32	40	36	33	32	31
	中	0.63	0.8	48	43	40	37	47	43	40	37	46	42	39	37	45	41	39	37	36
	否	0.56	1.0	51	47	44	41	50	46	43	41	49	45	43	41	47	45	42	40	39
			1.25	54	50	47	45	53	49	47	45	51	48	46	44	50	47	45	44	42
下方投影面積			1.5	56	52	49	47	55	51	49	47	53	50	48	46	52	49	47	46	45
			2.0	58	55	53	51	57	54	52	50	55	53	51	50	54	52	50	49	48
取付高さ	器具間隔最大限		2.5	59	57	55	53	58	56	54	53	57	55	53	52	55	54	52	51	50
	横方向 (A)	縦方向 (B)	3.0	60	58	56	55	59	57	56	54	58	56	55	53	56	55	54	53	51
Hm	1.26Hm	1.26Hm	4.0	61	60	58	57	61	59	58	57	59	58	56	55	57	56	55	54	53
			5.0	62	61	60	58	61	60	59	58	60	59	58	57	58	57	56	56	54
			7.0	63	62	61	60	62	61	60	60	60	60	59	58	59	58	58	57	55
			10.0	64	63	62	62	63	62	61	61	61	60	60	59	59	59	59	58	56

