

屋内照明器具特性

品番 (品名)	XF X440 NED+FSK41020									
光源	LED6500_85_2990 x1 2990.0 lm									
管理番号	K0199246(0)DR1									
BZ分類	BZ5/6.0/BZ6									

器具効率	100%	天井	80%				70%				50%				30%				0%		
	上方光束		12%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		88%		床	10%				10%				10%				10%			
室指数	照明率 (X0.01) ZCM																				
保守率	良	0.81	0.6	5.5	4.3	3.5	2.9	5.3	4.2	3.4	2.9	4.9	4.0	3.3	2.8	4.6	3.8	3.2	2.8	2.5	
	中	0.77	0.8	6.4	5.2	4.4	3.8	6.2	5.1	4.3	3.8	5.8	4.8	4.2	3.7	5.4	4.6	4.0	3.6	3.3	
	否	0.68	1.0	7.0	5.9	5.1	4.5	6.8	5.7	5.0	4.4	6.3	5.5	4.8	4.3	5.9	5.2	4.6	4.2	3.8	
			1.25	7.6	6.5	5.8	5.2	7.3	6.4	5.7	5.1	6.8	6.0	5.4	4.9	6.4	5.7	5.2	4.8	4.4	
下方投影面積	c m ²		1.5	7.9	7.0	6.3	5.7	7.7	6.8	6.1	5.6	7.2	6.5	5.9	5.4	6.7	6.1	5.6	5.2	4.8	
	等価発光面積		c m ²	2.0	8.5	7.7	7.0	6.5	8.2	7.5	6.9	6.4	7.7	7.1	6.6	6.1	7.2	6.7	6.3	5.9	5.4
取付高さ	器具間隔最大限		2.5	8.8	8.1	7.5	7.0	8.6	7.9	7.4	6.9	8.0	7.5	7.0	6.6	7.6	7.1	6.7	6.4	5.9	
	横方向 (A)	縦方向 (B)	3.0	9.1	8.5	7.9	7.4	8.8	8.2	7.7	7.3	8.3	7.8	7.4	7.0	7.8	7.4	7.1	6.7	6.2	
1.5m	1.59m	2.09m	4.0	9.4	8.9	8.4	8.0	9.1	8.7	8.2	7.9	8.6	8.2	7.9	7.5	8.1	7.8	7.5	7.2	6.7	
2	2.1	2.63	5.0	9.6	9.2	8.8	8.4	9.3	8.9	8.6	8.2	8.8	8.5	8.2	7.9	8.3	8.1	7.8	7.6	7.0	
2.5	2.61	3.19	7.0	9.8	9.5	9.2	8.9	9.6	9.3	9.0	8.7	9.1	8.8	8.6	8.3	8.6	8.4	8.2	8.0	7.4	
3	3.12	3.76	10.0	10.0	9.8	9.5	9.3	9.8	9.5	9.3	9.1	9.3	9.1	8.9	8.7	8.8	8.6	8.5	8.3	7.7	

